

Product show



1. مجموعة متنوعة من المواد الخام من قبل أ نسبة خلط معينة ، في القادوس



2. يتم تشكيله وتسخينه ليصبح - Pref المواد الخام المختلطة هي بلاطاً مسطحاً





3. ثم من خلال ضغط القالب ، يتم إدخال القالب ، التبريد ، من خلال آلة الجر ببطء



4. لتحقيق طول الاحتياجات المخصصة قطع. بعد الخروج الاصطناعي





Purplish Red



Brick Red



Sky Blue

















Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass	
2	Width deviation	mm	±0.5	0.2	Pass	
3	Thickness deviation	mm	±0.05	0.03	Pass	
4	Density	g/cm ³	1.170	1.170	Pass	
5	Tensile strength	MPa	≥1.0	1.1	Pass	
6	Elongation at break	%	≥1.0	1.1	Pass	
7	Holding full impact	kJ/m ²	—	—	Confirmed	Pass
8	Char temperature	°C	—	—	Confirmed	Pass
9	Flammability	—	—	—	Confirmed	Pass
10	Flame spread	—	—	—	Confirmed	Pass
11	Impact strength	kJ/m ²	—	—	Confirmed	Pass
12	Impact strength	kJ/m ²	—	—	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass	
2	Surface roughness	mm	0.1	0.1	Pass	
3	Tensile strength	MPa	≥1.0	1.1	Pass	
4	Elongation at break	%	≥1.0	1.1	Pass	
5	Flexural strength	MPa	≥1.0	1.1	Pass	
6	Flexural modulus	MPa	≥1.0	1.1	Pass	
7	Density	g/cm ³	1.170	1.170	Pass	
8	Heat stability	—	—	—	Confirmed	Pass
9	Char temperature	°C	—	—	Confirmed	Pass
10	Flammability	—	—	—	Confirmed	Pass
11	Flame spread	—	—	—	Confirmed	Pass
12	Impact strength	kJ/m ²	—	—	Confirmed	Pass
13	Impact strength	kJ/m ²	—	—	Confirmed	Pass
14	Impact strength	kJ/m ²	—	—	Confirmed	Pass
15	Impact strength	kJ/m ²	—	—	Confirmed	Pass



Our Factory





Our Customer



Packaging



FAQ

هل أنت منتج أم تاجر؟ *

نعم ، نحن مصنعون حقيقيون ، إذا كنت بحاجة إلى منتج خاص آخر ، فسوف نبذل قصارى جهدنا لمساعدتك ، حتى تتمكن من بناء علاقة تجارية طويلة الأمد.

هل يمكنني طلب المنتج مع أريد التوصيف؟ *

بالطبع يمكنك ذلك ، كما أننا سننتج المنتجات وفقاً لطلباتك التفصيلية *

هل يمكنك وضع العلامة التجارية لشركتي على منتجاتك؟ *

لكننا بحاجة إلى بعض المعلومات حول شركتكم ، ODM و OEM نعم ، نحن نقبل خدمة *

كيفية تثبيت لوح التسقيف؟ *

يرجى الاتصال بموظفي الخدمة لدينا ، لدينا فيديو التثبيت لك *

هل يمكنك تقديم عينات لي لفتح السوق واختبارها ؟؟؟؟؟ *

نعم نستطيع ذلك ، يمكننا تقديم عينات مجانية لك ، هل يمكنك دفع تكلفة الشحن ، يرجى الاتصال بموظفي *
الخدمة لدينا.

ما هو مصطلح التجارة الخاص بك؟ *

مقدما ، الرصيد قبل الشحن 30% T / T :الدفع *

• مهلة الإنتاج: في غضون 7 أيام عمل بعد إيداع 30

• ميناء الشحن فوب: فوشان ، وقوانغتشو ، وشنغتشو ، وشنغتشو