

مع عامل ومضافات مقاومة للأشعة فوق البنفسجية. من خلال التركيب العلمي ، المصنوع من PVC تي المواد الخام الرئيسية هي [مصنع بلاط سقف المنزل الصين](#) □ التكنولوجيا المتقدمة. □

1. □□□□ □□□□
2. □□□□□□ □□□□□□
3. waterproof □□□□ □
4. □□□□□□□□ □□□□□□
5. □□□□□□□□ □□□□□□□□
6. □□□□□□ □□□ □□□□



zxc roofing tile industry

# After sales less is really good

Ten years of slow fading, **30** years of warranty



## GOOD CHOICE

Our advantage



Intimate service, strong product supply capacity



product available



A variety of styles and specifications sufficient stock



Support customization



Specifications and sizes can be consulted with customer service in detail, and quotations can be customized



Worry-free after sales



Manufacturers wholesale quality assurance, affordable prices, worry-free after-sales

الاسقف	12 - 1
الاسقف	الاسقف
الاسقف	3.0-6.8 / الم
الاسقف	1130 الم 930 / الم 980 / الم 1050 / الم 1080 / الم
الاسقف	30 الم
الاسقف	الاسقف ASA PVC
الاسقف	الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف
الاسقف	الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف
الاسقف	1
الاسقف	-10 الم 70 الم الاسقف الاسقف
الاسقف	الاسقف الاسقف الاسقف الاسقف الاسقف الاسقف
الاسقف	2 الم 3 الم
الاسقف	10 الم الم الم

[انقر بولي كلوريد الفينيل بلاط السقف المورد الصين لتعلم المزيد](#)

# SOURCE MANUFACTURER #

---

>



# THE TROUBLES OF TRADITIONAL ROOF TILES

#

other products

×



## severely faded

Wind and sun soften and fade



## There is a gap

Uneven with gaps, leaking rain



## uneven color

Weathered uneven color  
phenomenon



## Fragile

Fragile and complicated  
to install

# our products ✓

Ten years of slow fading, 30 years of warranty



**Uniform color, durable and not easy to fade**  
Good quality, durable and bright.




high toughness



Strong pressure resistance

Effective insulation



good sound insulatio



**thermal and acoustic insulation high-quality**  
Good sound insulation effect in case of external noise



**preservative**  
Anti-acid and alkali



**flame retardant performance**  
b1 class fire performance

# PRODUCT PARAMETERS

---

#

>



**thickness:** 1.0mm-3.0mm

**width:** 1130/980/900/840/1080mm

**length:** customizable

**waveform:** big hang, small wave

**type:** asa plastic roofing tile

**Be applicable:** Factory buildings, ware houses, markets, residences, market roads, canopies, chemically corrosive factories

---



# A variety of colors, optional to build different architectural styles

More colors can be customized



<Mlight yellow>



<dark blue>



<grass green>



<Beige>



# CUSTOMER CASE SHOW #





本公司可承接各种 PVC 瓦、FRP 瓦、PC 瓦。



## Quality inspection instruments strictly control the quality

Each batch of products has undergone rigorous testing.



Gravity testing



Hardness testing



Tensile force testing



Impact resistance testing

Factory display



In-stock inventory



Own production line



Own production line



# Exhibition





# Certificate

# Official quality inspection, quality assurance

Multiple quality inspection and testing to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification



佛山市质量计量监督检测中心  
**检验报告**  
 报告号: QB-049-02  
 样品号: G14-WT1489  
 共 2 页 第 2 页

序号	检测项目	单位	标准要求	检测结果	判定
1	外观	—	表面光滑平整, 厚度均匀, 色泽一致, 无裂纹、缺口、鼓泡、烧焦、气痕、明显麻点、杂质点	符合	合格
2	密度	g/cm <sup>3</sup>	1.45~1.65	1.64	合格
3	弯曲性能	mm	支撑跨度800mm, 载荷40kg, 允许挠度≤50	15	合格
4	冲击性能	—	1kg重钢球, 1.5m自由落体, 冲击试样无裂纹, 试样经冲击试验后不得产生贯穿的孔穴或裂纹	符合	合格
5	吸水率	%	≥60	43	合格

审核: 王博斌  
 主检: 陈德聪  
**全部合格**

佛山市质  
 Foshan Supervision

# Packaging



# FAQ

\* 00000 00 0000 000 00  
 0 000 000 0000 000 000000 000 0000 .0000000 000000 00 000000 00 0000000 00000 0 00000000 0000000 0000 0 0000 \*

0000 00000000 0000 0000 0000000 000 0000000 00 \*

000000000 000 0000000 0000000000 00000000 000 000000 00 \*

