






ZXC Roof Tile Industry

Reliable quality and worry-free after-sales

# FRP LIGHTING ROOF TILE



***10-year  
warranty***



الخصائص العامة	الخصائص الفنية لمنتجات الفريبرم FRP-01	
الرمز	frp-01	
الوزن	الوزن	
الطول	6000 ملم (الطول القياسي) 11800 ملم (الطول المخصص)	
العرض	العرض القياسي 930 ملم	
السمك	840 ملم	
اللون	660 ملم	
الخواص الميكانيكية	1.0 ± 0.1 مم	
	1.2 ± 0.1 مم	
	1.5 ± 0.1 مم	
	2.0 ± 0.1 مم	
الخواص الفيزيائية	1.7 ± 0.1 2 / 1000	
	2.1 ± 0.1 2 / 1000	
	2.6 ± 0.1 2 / 1000	
	3.0 ± 0.1 2 / 1000	
الخواص الكيميائية		
SQ.M./20 (21) (معدل)	SQ.M./40 (26) (معدل)	
12000 2	15000 2	
10000 2	12300 (معدل)	
8000 2	10000 2	
7000 2	8600 2	

لتعلم المزيد [frp](#) انقر [مصنعي ألواح التسقيف](#)



# A variety of colors, can build different architectural styles

More colors can be customized



light yellow



blue



grass green





Beige



---

# PRODUCT DISPLAY

Authentic product photography highlights the quality of details





# CUSTOMER CASE SHOW

More than ten years of production experience





# APPLICABLE SCENE DISPLAY

scope of application

~



## *planting shed*

Rainproof, constant temperature  
moisturizing space, transparent



## *roof*

Good light transmission  
performance, no rain leakage



## *Villa shed*

Bright colors, more class



## *Recreation area*

Color unevenness due to weathering



# SIX REASONS TO CHOOSE US

“

Iron tiles can be directly covered



*sound  
insulation*

*Anti  
-corrosion*

*insulation*

*High  
temperature  
resistance*

*anti  
-stress*



# “ SIX PROPERTIES ”

Good quality and low price. Quality assurance, trustworthy



## 01 High temperature resistance, frost crack resistance

The product is a solid molecular material, and the operating temperature is -40°-120°



## 02 Strong bearing capacity, more impact resistance

Add high quality glass fiber



## 03 Iron tiles can be directly covered

Exclusive research and development technology, more cost-saving.





## **04** Impact resistance

Shock resistant, not easy to break



## **05** Good flame retardant performance

Maintain stable performance in the temperature range of  $-40^{\circ}$ - $120^{\circ}$  without softening










# FACTORY REAL SHOT DISPLAY

Professional production to do every step





# Sampling and testing each batch of products to ensure quality

X



DISPLAY

# CUSTOM PROCESS

Easy shopping, quality assurance,  
after-sales rest assured



01

## ONLINE CONSULTATION

Provide professional product  
consultation



02

## PROVIDE PRICING

Provide reasonable price for  
product performance

03

## PREPAID CUSTOMIZATION

Deposit in advance according  
to different proportions







— **04** —

**ORDER  
PRODUCTION**

Professional and rapid production  
of multiple production lines

— **05** —

**AFTER  
DELIVERY**

Intimate and assured after-sales  
service



**Exhibition**





# Certificate

# Security sense of authoritative testing

## Multiple quality inspection and testing to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification





# Packaging



# FAQ

\* 00000 00 0000 000 00  
 0 000 000 0000 000 00000 000 0000 .0000000 000000 00 000000 00 0000000 0000 0 00000000 0000000 0000 0 0000 \*

0000 00000000 0000 0000 0000000 000 0000000 00 \*

000000000 000 0000000 000000000 00000000 000 000000 00 \*

