

Product show



1. A variety of raw materials by a certain percentage mixing, into the hopper



2. The mixed raw materials are pre-formed and heated to become flat tiles



3. Then through the mold pressure, elastic the molding, cooling, through the traction machine slowly introduced



4. To achieve the length of customer needs, cut after artificial out

nombre del producto	Spanish Style ASA Roof Tile
Marca	ZXC
Lugar de origen	Foshan city, Guangdong province, China (Mainland)
Material	Acrylonitrile Styrene acrylate copolymer, Polivinilo cloruro, Calcium powder, other chemical materials
Garantizar	25 años
Certificación	ISO9001 / SGS / CE
Cantidad mínima de pedido	100 square meter
El tiempo de entrega	1x20GP for 6 days, 1x40GP for 7 days
Supply Ability	We have 8 produce lines, about 13500 square meter every day
Términos de pago	T/T , firstly pay 30% deposit, before loading container pay rest of payment L/C ,
Envío	Full Container Load (FCL) Service, We do it by myself. Less than Container Load (LCL) Service, We find our agents to do it.
Paquete	Pallet or PE bag
Puerto	Guangzhou / Shenzhen / Foshan
Solicitud	Villa roofing, House roofing, Garden, Grange, Container house, Flat to Slope Project, Etc
Número de modelo	#1050-160-30
Tipo	Spanish Style
Ancho promedio	1050mm
Effective Width	960mm

Grosor	2.3mm / 2.5mm / 2.8mm / 3.0mm
Largo	Debe ser un multiple of sección
Color	Orange / Red / Grey / Sky blue / Dark green
Wave Spacing	160mm
Altura de las olas	30mm
Section Length	219mm

Estructura

Surface: Imported ASA raw materials from the world's top 500 GE company, Super weather resistance, truly 10 years don't have color fading. The standard is that the thickness of the surface reaches 0.15mm, We can reach 0.15-0.18mm.

Medium: The material is Polivinilo cloruro y Calcium powder, the proportion is 1:1. This is the best ratio after many trials. This ratio guarantees the strength and toughness of the product.

Bottom: The important material also is Polivinilo cloruro y Calcium powder, but add other chemical materials. We are make the same color as the surface color and white color. Gloss of products is best in the industry.

Rasgo

- **De larga duración Color (en menos 10 años)**
- The product features ultra durability in natural environment. Even under tough conditions of exposure to UV, high temperature and freezing coldness, it still keeps stable color.
- **Excllent Anti-corrosion performance**
- Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc. Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.
- **Good Waterproofing Performance**
- Synthetic Resin Tile selects highly weater-resistant resin, which is dense and absorbing no water, with no pore penetration problem. The product is 45% wider than traditional tiles with less roof contact, so synthetic resin, s waterproof performance has greatly increased than traditional losas.
- **Strong Fire Resistance**
- Belonging flame retardant material, with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.
- **Excellent Heat Insulating Property**
- The heat conductivity coefficient is 0.325w/m.k, about 1/300 of clay tile ,1/50 of cement tile, and 1/2000 of thick color steel tile. Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.
- **Good sound insulation**
- Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.





Purplish Red



Brick Red



Sky Blue











Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm ³	---	1.170	---
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Holding full impact	kJ/m ²	---	---	Confirmed
8	Char temperature	°C	---	---	Confirmed
9	Flammability	---	---	---	Confirmed
10	Flame spread	---	---	---	Confirmed
11	Impact strength	kJ/m ²	---	---	Confirmed
12	Impact strength	kJ/m ²	---	---	Confirmed
13	Impact strength	kJ/m ²	---	---	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural deflection	MPa	≥1.0	1.1	Pass
7	Density	g/cm ³	---	1.170	---
8	Heat stability	°C	---	---	Confirmed
9	Heat stability	°C	---	---	Confirmed
10	Heat stability	°C	---	---	Confirmed
11	Heat stability	°C	---	---	Confirmed
12	Heat stability	°C	---	---	Confirmed
13	Heat stability	°C	---	---	Confirmed
14	Heat stability	°C	---	---	Confirmed
15	Heat stability	°C	---	---	Confirmed
16	Heat stability	°C	---	---	Confirmed
17	Heat stability	°C	---	---	Confirmed
18	Heat stability	°C	---	---	Confirmed
19	Heat stability	°C	---	---	Confirmed
20	Heat stability	°C	---	---	Confirmed



Our Factory





Our Customer



Packaging



FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

*** Sí, aceptamos el servicio OEM y ODM. Pero necesitamos información sobre su empresa.**

***¿Cómo instalar la hoja de techos?**

***Póngase en contacto con nuestro personal de servicio, tenemos un video de instalación para usted.**

***¿Puede proporcionarme muestras para abrir el mercado y probar? ¿calidad?**

***Sí, podemos. Podemos proporcionarle muestras gratuitas, ¿podría pagar el costo de envío? Comuníquese con nuestro personal de servicio.**

***¿Cuál es su término comercial?**

*** Pago: T/T 30% por adelantado, saldo antes del envío.**

• Tiempo de entrega de producción: dentro de los 7 días hábiles después del 30% de depósito

• Puerto de envío FOB: Foshan, Guangzhou, Shenzhen