

Product show



1. Une variété de matières premières par un certain pourcentage de mélange, dans la trémie



2. Les matières premières mélangées sont préférées -formées et chauffées pour devenir des tuiles plates



3. Ensuite, à travers la pression du moule, le moulage élastique, le refroidissement, à travers la machine de traction lentement introduite



4. Pour atteindre la longueur des besoins des clients couper. après une sortie artificielle







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm ³	—	1.170	—
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥2.0	3.1	Pass
7	Holding full impact	kJ/m ²	—	—	Confirmed
8	Char temperature	°C	—	—	Confirmed
9	Flammability	—	—	—	Confirmed
10	Flame spread	—	—	—	Confirmed
11	Impact strength	kJ/m ²	—	—	Confirmed
12	Impact strength	kJ/m ²	—	—	Confirmed
13	Impact strength	kJ/m ²	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks, visible impurities, or other defects.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥2.0	3.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural modulus	MPa	≥1.0	1.1	Pass
7	Density	g/cm ³	—	1.170	—
8	Heat stability	—	—	—	Confirmed
9	Char temperature	°C	—	—	Confirmed
10	Flammability	—	—	—	Confirmed
11	Flame spread	—	—	—	Confirmed
12	Impact strength	kJ/m ²	—	—	Confirmed
13	Impact strength	kJ/m ²	—	—	Confirmed
14	Impact strength	kJ/m ²	—	—	Confirmed
15	Impact strength	kJ/m ²	—	—	Confirmed



Our Factory





Our Customer



Packaging



FAQ

* **Vous êtes fabricant ou commerçant ?**

* **Oui, nous sommes un vrai fabricant, il y a beaucoup de photos dans l'introduction de notre société. Si vous avez besoin d'un autre produit spécial, nous ferons de notre mieux pour vous aider, afin que nous puissions établir une relation commerciale à long terme.**

* **Puis-je commander le produit avec je veux profiler ?**

* **Naturellement vous pouvez, également nous produisons les produits selon vos demandes de détail.**

- * **Pouvez-vous mettre la marque de mon entreprise sur vos produits ?**
- * **Oui, nous acceptons le service OEM & ODM. Mais nous avons besoin d'informations sur votre entreprise.**
- * **Comment installer la tôle de toiture?**
- * **Veillez contacter notre personnel de service, nous avons une vidéo d'installation pour vous.**
- * **Pouvez-vous me fournir des échantillons pour ouvrir le marché et tester qualité?**
- * **Oui, nous pouvons. Nous pouvons vous fournir des échantillons gratuits, pourriez-vous payer les frais d'expédition ? Veillez contacter notre personnel de service.**
- * **Quel est votre terme commercial?**
- * **Paiement : T/T 30 % à l'avance, solde avant expédition.**
- **Délai de production : dans les 7 jours ouvrables après dépôt de 30 %**
- **Port d'expédition FOB : Foshan, Guangzhou, Shenzhen**