
Product show

Design	Spanish style
Color Lasting[]	10 years no fading
Length	customized
Thickness	1.8mm, 2.0mm, 2.2mm, 2.5mm, 2.8mm, 3.0mm
Overall width[]	1130mm
Effective width	1000/1050mm
Purlin spacing[]	660mm
Layers	3 layers
Surface	Embossed/Smoothsurface




More Types


1130 corrugaetd sheets



1130 trapezoidal sheets





900 high wave



980 high wave

80 30






ZXC New Material Technology Co., Ltd. Our products include PVC sheets, ASA Synthetic Resin Roof Tile, FRP Roofing Tiles, gutter, upvc roofing sheets etc. If your order matches our stock size details, we can faster delivery time. Welcome Contact Us Custom. (pvc corrugated sheet manufacturer)



Engineering case



Certificate







FAQ

*Are you manufacturer or trader?

*Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.

*Can I order the product with i want to profile?

*Of course you can, also we will produce the products according to your detail requests.

*Can you put my company's brand on your products?

*Yes, we are accept OEM&ODM service. But we need some information about your company.

*How to install the roofing sheet?

*Please contact our service staff, we have installation video for you.

*Can you provide samples for me to open the market and test quality?

*Yes,we can.We can provide free samples to you.

*Could you pay the shipping cost?

Please contact our service staff.

*What is your trade term?

* Payment: T/T 30% in advance, balance before shipment.

? Production Lead Time: Within 7 working days after 30% deposit

? FOB Shipping Port: Foshan, Guangzhou, Shenzhen

ZXC New Material Technology Co., Ltd. is clear plastic roof sheets supplier China, Our products include PVC sheets, ASA Synthetic Resin Roof Tile, FRP Roofing Tiles, gutter etc. If your order matches our stock size details, we can faster delivery time.

Product show





Product Name	Spanish Style ASA Roof Tile			
Brand	ZXC			
Place of Origin	Foshan city,Guangdong province,China(Mainland)			
Material	Acrylonitrile Styrene acrylate copolymer,Polyvinyl chloride, Calcium powder,other chemical materials			
Guarantee	25 years			
Certification	ISO9001 / SGS / CE			
Minimum Order Quantity	100 square meter			
Delivery Time	1x20GP for 6 days,1x40GP for 7 days			
Supply Ability	We have 8 produce lines, about 13500 square meter every day			
Payment Terms	T/T , firstly pay 30% deposit,before loading container pay rest of payment L/C ,			
Shipping	Full Container Load (FCL) Service,We do it by myself. Less than Container Load (LCL) Service,We find our agents to do it.			
Package	Pallet or PE bag			
Port	Guangzhou / Shenzhen / Foshan			
Application	Villa roofing,House roofing,Garden,Grange,Container house, Flat to Slope Project,Etc			

Model Number	#1050-160-30
Туре	Spanish Style
Overall Width	1050mm
Effective Width	960mm
Thickness	2.3mm / 2.5mm / 2.8mm / 3.0mm
Length	Must be a multiple of section
Color	Orange / Red / Grey / Sky blue / Dark green/Customized
Wave Spacing	160mm
Wave Height	30mm
Section Length	219mm
Purlin Spacing	660mm

More Types



The ASA Layer The Backbone Layer The Abrasion Resistance Layer Self-cleaning

Structure

Surface:Imported ASA raw materials from the world's top 500 GE company,Super weather resistance, truly 10 years don,t have color fading.The standard is that the thickness of the surface reaches 0.15mm,We can reach 0.15-0.18mm.

Medium:The material is Polyvinyl chloride and Calcium powder,the proportion is 1:1.This is the best ratio after many trials.This ratio guarantees the strength and toughness of the product.

Bottom:The important material also is Polyvinyl chloride and Calcium powder,but add other chemical materials.We are make the same color as the surface color and white color.Gloss of products is best in the industry.

Feature

· Long-lasting Color (at least 10 years)

 \cdot The product features ultra durability in natural environment. Even under tough conditions of exposure to UV, high temperature and freezing coldness, it still keeps stable color.

\cdot Excllent Anti-corrosion performance

 \cdot Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc.Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.

Good Waterproofing Performance

 \cdot Synthetic Resin Tile selects highly weater-resistant resin, which is dense and absorbing no water, with no pore penetration problem. The product is 45% wider than traditional tiles with less roof contact, so synthetic resin, s waterproof performance has greatly increased than traditional tiles.

• Strong Fire Resistance

 \cdot Belonging flame retardant material, with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.


\cdot Excellent Heat Insulating Property

 \cdot The heat conductivity coefficient is 0.325w/m.k,about 1/300 of clay tile ,1/50 of cement tile,and 1/2000 of thick color steel tile. Therefore without condidering ading heat-preserving layer , the heat insulation and heat preservation of synthetic resin tile can still be optimized.

\cdot Good sound insulation

 \cdot Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.

resin roof tile saccessories





Engineering case



Certificate





Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load Capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300

Feature:

- 1. Excllent Anti-corrosion Performance
- 2.Good Waterproof Performance
- 3.Fire Resistance
- 4.Heat insulation
- 5.Sound ins ulation
- 6.Weather fastness, ageing resistance

Package: Nude or standard export package



*Are you manufacturer or trader?

*Yes, we are real , there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.

*Can I order the product with i want to profile?

*Of course you can, also we will produce the products according to your detail requests.

*Can you put my company's brand on your products?

*Yes,we are accept OEM&ODM service.But we need some information about your company.

*How to install the roofing sheet?

*Please contact our service staff, we have installation video for you.

*Can you provide samples for me to open the market and test quality?

*Yes,we can.We can provide free samples to you ,Could you pay the shipping cost?Please contact our service staff.

*What is your trade term?

- * Payment: T/T 30% in advance, balance before shipment.
- ? Production Lead Time: Within 7 working days after 30% deposit
- ? FOB Shipping Port: Foshan, Guangzhou, Shenzhen