

Product show



1. Pelbagai bahan mentah oleh a peratusan tertentu mencampurkan, ke dalam corong



2. Bahan mentah campuran adalah pref -dibentuk dan dipanaskan untuk menjadi jubin rata



3. Kemudian melalui tekanan acuan, lastik acuan, penyejukan, melalui mesin tarikan perlahan-lahan diperkenalkan



4. Untuk mencapai panjang keperluan pelanggan potong. selepas keluar buatan







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	---	The color of the sheet is uniform. There should be no defects, such as visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass	
2	Wall thickness	mm	1.5	1.5	Pass	
3	Thickness deviation	mm	±0.1	±0.1	Pass	
4	Density	g/cm ³	1.25	1.25	Pass	
5	Tensile strength	MPa	≥20	20	Pass	
6	Elongation at break	%	≥20	20	Pass	
7	Holding full impact	kJ/m ²	---	---	Confirmed	Pass
8	Char temperature	°C	---	---	Confirmed	Pass
9	Char residue	%	---	---	Confirmed	Pass
10	Flammability	---	---	---	Confirmed	Pass
11	Flammability	---	---	---	Confirmed	Pass
12	Flammability	---	---	---	Confirmed	Pass
13	Flammability	---	---	---	Confirmed	Pass
14	Flammability	---	---	---	Confirmed	Pass
15	Flammability	---	---	---	Confirmed	Pass
16	Flammability	---	---	---	Confirmed	Pass
17	Flammability	---	---	---	Confirmed	Pass
18	Flammability	---	---	---	Confirmed	Pass
19	Flammability	---	---	---	Confirmed	Pass
20	Flammability	---	---	---	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The surface should be smooth and uniform. There should be no visible defects, such as visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥20	20	Pass
4	Elongation at break	%	≥20	20	Pass
5	Flexural strength	MPa	≥20	20	Pass
6	Flexural modulus	MPa	≥2000	2000	Pass
7	Density	g/cm ³	1.25	1.25	Pass
8	Heat stability	°C	170	170	Pass
9	Heat stability	°C	170	170	Pass
10	Heat stability	°C	170	170	Pass
11	Heat stability	°C	170	170	Pass
12	Heat stability	°C	170	170	Pass
13	Heat stability	°C	170	170	Pass
14	Heat stability	°C	170	170	Pass
15	Heat stability	°C	170	170	Pass
16	Heat stability	°C	170	170	Pass
17	Heat stability	°C	170	170	Pass
18	Heat stability	°C	170	170	Pass
19	Heat stability	°C	170	170	Pass
20	Heat stability	°C	170	170	Pass



Our Factory





Our Customer



Packaging



FAQ

* Adakah anda pengilang atau peniaga?

* Ya, kami adalah pengeluar sebenar, terdapat banyak gambar dalam pengenalan syarikat kami. jika anda memerlukan produk istimewa lain, kami akan melakukan yang terbaik untuk membantu anda, supaya kami boleh membina hubungan perniagaan jangka panjang.

* Bolehkah saya memesan produk dengan saya ingin membuat profil?

* Sudah tentu anda boleh, juga kami akan menghasilkan produk mengikut permintaan butiran anda.

- * **Bolehkah anda meletakkan jenama syarikat saya pada produk anda?**
- * **Ya, kami menerima perkhidmatan OEM & ODM. Tetapi kami memerlukan beberapa maklumat tentang syarikat anda.**
- * **Bagaimana untuk memasang lembaran bumbung?**
- * **Sila hubungi kakitangan perkhidmatan kami, kami mempunyai video pemasangan untuk anda.**
- * **Bolehkah anda menyediakan sampel untuk saya membuka pasaran dan menguji kualiti?**
- * **Ya, kami boleh. Kami boleh memberikan sampel percuma kepada anda, Bolehkah anda membayar kos penghantaran? Sila hubungi kakitangan perkhidmatan kami.**
- * **Apakah istilah perdagangan anda?**
- * **Pembayaran: T/T 30% terlebih dahulu, baki sebelum penghantaran.**
- **Masa Utama Pengeluaran: Dalam tempoh 7 hari bekerja selepas deposit 30%.**
- **Pelabuhan Penghantaran FOB: Foshan, Guangzhou, Shenzhen**