Product show

1.A variety of raw materials by a certain percentage mixing, intohe hopper	2. The mixed raw materials are pref -ormed and heated to become flat tiles
3. Then through the mold pressure,lastic the molding, cooling, throughthe traction machine slowly introduced	4.To achieve the length of customerneeds putulin. after artificial out

pangalan ng Produkto	Estilo ng Espanyol Asa Roof Tile
Tatak	ZXC
Lugar ng Pinagmulan	Foshan City, Lalawigan ng Guangdong, China (Mainland)
Materyal	Acrylonitrile Styrene acrylate copolymer,Polyvinyl chloride, Calcium powder,other chemical materials
Garantiya	25 taon
Sertipikasyon	ISO9001 / SGS / CE
Minimum na dami ng order	100 square meter
Oras ng paghatid	1x20gp para sa 6 na araw, 1x40gp sa loob ng 7 araw
Kakayahan ng supply	Mayroon kaming 8 gumawa ng mga linya, mga 13500 square meter araw -araw
Kasunduan sa pagbabayad	T/T, unang magbayad ng 30% na deposito, bago mag -load ng lalagyan ng bayad sa pagbabayad L/C ,
Pagpapadala	Buong serbisyo ng lalagyan ng pag -load (FCL), ginagawa namin ito sa aking sarili. Mas mababa sa serbisyo ng lalagyan ng pag -load (LCL), nahanap namin ang aming mga ahente na gawin ito.
Package	Pallet o PE bag
Port	Guangzhou / Shenzhen / Foshan
Application	Villa Roofing, House Roofing, Garden, Grange, Container House, Flat sa slope project, atbp
Numero ng modelo	#1050-160-30

I -type	Estilo ng Espanyol
Pangkalahatang lapad	1050mm
Mabisang lapad	960mm
Kapal	2.3mm / 2.5mm / 2.8mm / 3.0mm
Haba	Must be a multiple of section
Kulay	Orange / pula / kulay abo / langit asul / madilim na berde
Wave spacing	160mm
Taas ng alon	30mm
Haba ng seksyon	219mm

Istraktura

Surface:Imported ASA raw materials from the world's top 500 GE company,Super weather resistance, truly 10 years don,t have color fading.The standard is that the thickness of the surface reaches 0.15mm,We can reach 0.15-0.18mm.

Medium:The material is Polyvinyl chloride and Calcium powder,the proportion is 1:1.This is the best ratio after many trials.This ratio guarantees the strength and toughness of the product.

Bottom:The important material also is Polyvinyl chloride and Calcium powder,but add other chemical materials.We are make the same color as the surface color and white color.Gloss of products is best in the industry.

Tampok

· Long-lasting Kulay (at least 10 years)

· The product features ultra durability in natural environment.Even under tough conditions of exposure to UV,high temperature and freezing coldness,it still keeps stable color.

· Excllent Anti-corrosion performance

· Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc.Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.

· Good Waterproofing Performance

· Synthetic Resin Tile selects highly weater-resistant resin,which is dense and absorbing no water,with no pore penetration problem.The product is 45% wider than traditional tiles with less roof contact,so synthetic resin,s waterproof performance has greatly increased than traditional tiles.

· Strong Fire Resistance

· Belonging flame retardant material,with fire resistance ≥ B1 as tested by national authoritative departments according to GBB8624-2006 standard.

· Excellent Heat Insulating Property

· The heat conductivity coefficient is 0.325w/m.k,about 1/300 of clay tile ,1/50 of cement tile,and 1/2000 of thick color steel tile.Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.

· Good sound insulation

· Ang mga pagsubok ay napatunayan na ang mga synthetic resin tile ay may mahusay na pag -andar ng pagsipsip ng ingay kapag nagdusa ng malakas na pag -ulan at malakas na hangin.







Purplish Red | Brick Red | Sky Blue | Black | Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm－3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excllent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories

Certificate

Our Factory

Our Customer

Packaging

FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

*** Oo, tinatanggap namin ang serbisyo ng OEM & ODM. Ngunit kailangan namin ng ilang impormasyon tungkol sa iyong kumpanya.**

***Paano i -install ang sheet ng bubong?**

***Mangyaring makipag -ugnay sa aming mga kawani ng serbisyo, mayroon kaming video sa pag -install para sa iyo.**

***Maaari ba kayong magbigay ng mga sample para sa akin upang buksan ang merkado at pagsubok kalidad?**

***Oo, maaari kaming magbigay ng mga libreng sample sa iyo, maaari mo bang bayaran ang gastos sa pagpapadala? Mangyaring makipag -ugnay sa aming mga kawani ng serbisyo.**

***Ano ang iyong termino sa kalakalan?**

*** Pagbabayad: T/T 30% nang maaga, balanse bago ang kargamento.**

• Oras ng tingga ng produksyon: Sa loob ng 7 araw ng pagtatrabaho pagkatapos ng 30% na deposito

• Fob Shipping Port: Foshan, Guangzhou, Shenzhen