

# Product show



1. 聚碳酸酯 (PC) 原料

2. 聚碳酸酯 (PC) 原料 - 原料



3. 聚碳酸酯 (PC) 原料

4. 聚碳酸酯 (PC) 原料

原料	聚碳酸酯 (PC) ASA 原料
厚度	25mm
规格	ISO9001/CE
重量	100kg
长度	1x20GP 6m, 1x40GP 7m
宽度	8m, 1350mm
颜色	红 / T 30% 紫外线吸收剂, 阻燃, 防霉, 防藻
包装	Full Container Load (FCL) 或 Less than Container Load (LCL)
材料	PE
表面处理	UV 涂层 / 防霉 / 防藻
应用	屋顶, 棚顶, 遮阳, Grange, 装饰, 透光, 隔音, 隔热, Flat to Slope
型号	#1050-160-30
重量	1050kg
长度	960m
宽度	2.3m, 2.5m, 2.8m, 3.0m







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

# Accessories







# Certificate



Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm <sup>3</sup>	—	1.170	—
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥2.0	3.1	Pass
7	Holding full impact	kJ/m <sup>2</sup>	—	—	Confirmed
8	Char temperature	°C	—	—	Confirmed
9	Flammability (UL94)	—	—	—	Confirmed
10	Flammability (UL94)	—	—	—	Confirmed
11	Flammability (UL94)	—	—	—	Confirmed
12	Flammability (UL94)	—	—	—	Confirmed
13	Flammability (UL94)	—	—	—	Confirmed
14	Flammability (UL94)	—	—	—	Confirmed
15	Flammability (UL94)	—	—	—	Confirmed
16	Flammability (UL94)	—	—	—	Confirmed
17	Flammability (UL94)	—	—	—	Confirmed
18	Flammability (UL94)	—	—	—	Confirmed
19	Flammability (UL94)	—	—	—	Confirmed
20	Flammability (UL94)	—	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥2.0	3.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural modulus	MPa	≥1.0	1.1	Pass
7	Density	g/cm <sup>3</sup>	—	1.170	—
8	Heat stability	°C	—	—	Confirmed
9	Heat stability	°C	—	—	Confirmed
10	Heat stability	°C	—	—	Confirmed
11	Heat stability	°C	—	—	Confirmed
12	Heat stability	°C	—	—	Confirmed
13	Heat stability	°C	—	—	Confirmed
14	Heat stability	°C	—	—	Confirmed
15	Heat stability	°C	—	—	Confirmed
16	Heat stability	°C	—	—	Confirmed
17	Heat stability	°C	—	—	Confirmed
18	Heat stability	°C	—	—	Confirmed
19	Heat stability	°C	—	—	Confirmed
20	Heat stability	°C	—	—	Confirmed



# Our Factory





# Our Customer





\* 請提供詳細的技術規格書 **OEM** 或 **ODM** 服務，並說明相關的專利權、商標權及法律責任歸屬。

\* 請提供相關的認證或測試報告？

\* 請提供相關的產品照片或樣品，並說明相關的包裝及運輸要求。

\* 請提供相關的產品說明書或技術資料，並說明相關的安裝及維護要求？

\* 請提供相關的產品價格表，並說明相關的折扣及優惠政策。請提供相關的產品目錄或產品清單，並說明相關的產品型號及規格。

\* 請提供相關的產品包裝設計圖？

\* 請提供相關的產品規格：**T / T** 或 **30%** 預付款項。

• 請提供相關的產品規格：**7** 天內提供樣品 **30%**

• **FOB Shipping Port:** 請提供相關的產品包裝及運輸要求。