Product show

1.A variety of raw materials by a certain percentage mixing, intohe hopper	2. The mixed raw materials are pref -ormed and heated to become flat tiles
3. Then through the mold pressure,lastic the molding, cooling, throughthe traction machine slowly introduced	4.To achieve the length of customerneeds cut off. after artificial out

□□□□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	ZXC
□□□□□□□□□□□□□□	Foshan City, □□□□□□□□□□□□□□□□□□□□□□□□, □□□ (□□□□□□□□□□□□)
□□□□□	Acrylonitrile Styrene acrylate copolymer,,Polyvinyl chloride,, Calcium powder,other chemical materials
□□□□□□□□□	25 □□
□□□□□□□□□	ISO9001 / SGS / CE
□□□□□□□□□□□□□□□□□□□□□ □□□□	100 □□□□□□□□□□□
□□□□□□□□□□	1x20gp □□□□□□□□ 6 □□□ 1x40gp □□□□□□□□ 7 □□□
□□□□□□□□□□□□□□□□□□□□	□□□□□□ 8 □□□□□□□□□□□□□ 13500 □□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□	t/t, □□□□□□□□□□□□□□□□□□□ 30% □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□ L/C ,
□□□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ (FCL) □□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□ (LCL) □□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□	□□□□□□□□□□□□□□□□ PE
□□□□□□□	□□□□□□□ / □□□□□□□□□ / Foshan
□□□□□□□□□□□	□□□□□□□□□□□□□, □□□□□□□□□□□, □□□, Grange, □□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□ □□□
□□□□□□□□□□□	#1050-160-30
□□□□□	□□□□□□□□□
□□□□□□□□□□□□□□□	1050 □□.

[illegible]	960 [illegible].
[illegible]	2.3 [illegible]. / 2.5 [illegible]. / 2.8 [illegible]. / 3.0 [illegible].
[illegible]	Must be a multiple of [illegible]
[illegible]	[illegible] / [illegible] / [illegible] / [illegible] / [illegible]
[illegible]	160 [illegible].
[illegible]	30 [illegible].
[illegible]	219 [illegible].

[illegible]

Surface:Imported ASA raw materials from the world's top 500 GE company,Super weather resistance, truly 10 years don,t have color fading.The standard is that the thickness of the surface reaches 0.15mm,We can reach 0.15-0.18mm.

Medium:The material is Polyvinyl chloride [illegible] Calcium powder,the proportion is 1:1.This is the best ratio after many trials.This ratio guarantees the strength and toughness of the product.

Bottom:The important material also is Polyvinyl chloride [illegible] Calcium powder,but add other chemical materials.We are make the same color as the surface color and white color.Gloss of products is best in the industry.

[illegible]

- [illegible] [illegible] ([illegible] [illegible] 10 [illegible])
- The product features ultra durability in natural environment.Even under tough conditions of exposure to UV,high temperature and freezing coldness,it still keeps stable color.

- Excllent Anti-corrosion performance
- Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc.Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.

- Good Waterproofing Performance
- Synthetic Resin Tile selects highly weater-resistant resin,which is dense and absorbing no water,with no pore penetration problem.The product is 45% wider than traditional tiles with less roof contact,so synthetic resin,s waterproof performance has greatly increased than traditional tiles.

- Strong Fire Resistance
- Belonging flame retardant material,with fire resistance ≥ B1 as tested by national authoritative departments according to GBB8624-2006 standard.

- Excellent Heat Insulating Property
- The heat conductivity coefficient is 0.325w/m.k,about 1/300 of clay tile ,1/50 of cement tile,and 1/2000 of thick color steel tile.Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.

- Good sound insulation
- [illegible]







Purplish Red | Brick Red | Sky Blue | Black | Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm－3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excllent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories

Certificate

Our Factory

Our Customer

Packaging

FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

* [illegible] OEM & ODM [illegible] [illegible] [illegible]

*[illegible]?

*[illegible].

*[illegible] [illegible]?

*[illegible]
[illegible]

*[illegible]?

* [illegible]: T/T 30% [illegible]

•[illegible]: [illegible] 7 [illegible] 30%

• FOB Shipping Port: Foshan, [illegible], [illegible]