





Ürün adı	ZXC round wave and trapezoid PVC roofing sheet in different colors
Marka	ZXC
Anavatan	Foshan city,Guangdong province,China(Mainland)
Malzeme	Polyvinyl chloride,Calcium powder,other chemical materials
Garanti	10 yıl
Certification	ISO9001 / SGS / CE
minimum sipariş miktarı	300 square meter
Teslimat süresi	1x20GP for 6 days,1x40GP for 7 days
Supply Ability	We have 8 produce lines,about 13500 square meter every day
Ödeme şartları	T/T , firstly pay 30% deposit,before loading container pay rest of payment L/C ,
Nakliye	Full Container Load (FCL) Service,We do it by myself. Less than Container Load (LCL) Service,We find our agents to do it.
Paket	Pallet or PE bag
Liman	Guangzhou / Shenzhen / Foshan
Başvuru	Factory,Warehouse,Farm,Market,Aisle.Especially in corrosive chemical plants, smelters, ceramic plants, soy sauce factory, chemical plants, printing and dyeing plant, organic solvent factory, acid, alkali and other corrosive plant




Model numarası	#1130-210-24
Tip	Trapezoid type
Overall Width	1130mm

Effective Width	1050mm
Kalınlık	1.3mm / 1.5mm / 1.8mm / 2.0mm / 2.3mm / 2.5mm / 2.8mm / 3.0mm
Uzunluk	5.8meter / 11.8meter / Customized
Renk	White / Blue / Green / Red / Customized
Wave Spacing	210mm
Dalga yüksekliđi	24mm
Katman	One layer / Two layers / Three layers







Özellik

• Anti korozyon

• ZhongXingCheng PVC plastic roofing sheet in the long term against acid, alkali, salt and other corrosive chemicals. Experiments prove that: In the salt, alkali and 60% following a 24-hour soaking in acid, no chemical reaction. Very suitable for acid rainprone areas and coastal use, the effect was particularly significant.

• Su geçirmez

• ZhongXingCheng PVC plastic roofing sheet's surface materials is co-extruded in ultra-weather surface layer resin to ensure the durability of products (for 15 years in quality assurance).

• Fire Resistance

• ZhongXingCheng PVC plastic roofing sheet is a flame retardant materials, through the national fire authority of the department according to GB8624-2006 standards for testing, fire safety performance \geq B1 grade.

• Isı yalıtımı

• ZhongXingCheng PVC plastic roofing sheet's thermal conductivity coefficient is 0.325w/mk, clay tile is about 1 / 310, cement tile 1 / 5, 0.5mm thick color steel tile 1 / 2000. Therefore, without considering the case of insulation layer increases, the PVC plastic roofing sheet can still achieve the best thermal insulation properties.

• Ses yalıtımı

• The tests prove that: in suffering heavy rain, high winds the impact of outside noise, ZhongXingCheng PVC plastic roofing sheet has a good absorption of the noise effect, noise down 30dB than color steel tile.

