


tên sản phẩm	ZXC round wave and trapezoid PVC roofing sheet in different colors
Thương hiệu	ZXC
Nguồn gốc	Foshan city,Guangdong province,China(Mainland)
Vật chất	Polyvinyl chloride,Calcium powder,other chemical materials
Bảo hành	10 năm
Certification	ISO9001 / SGS / CE
Số lượng đặt hàng tối thiểu	300 square meter
Thời gian giao hàng	1x20GP for 6 days,1x40GP for 7 days
Khả năng cung cấp	We have 8 produce lines,about 13500 square meter every day
Payment Terms	T/T , firstly pay 30% deposit,before loading container pay rest of payment L/C ,
Đang chuyển hàng	Full Container Load (FCL) Service,We do it by myself. Less than Container Load (LCL) Service,We find our agents to do it.
Bưu kiện	Pallet or PE bag
Hải cảng	Guangzhou / Shenzhen / Foshan
Ứng dụng	Factory,Warehouse,Farm,Market,Aisle.Especially in corrosive chemical plants, smelters, ceramic plants, soy sauce factory, chemical plants, printing and dyeing plant, organic solvent factory, acid, alkali and other corrosive plant




Số mô hình



#1130-210-24

Thể loại

Trapezoid type

Overall Width	1130mm
Effective Width	1050mm
Độ dày	1.3mm / 1.5mm / 1.8mm / 2.0mm / 2.3mm / 2.5mm / 2.8mm / 3.0mm
Chiều dài	5.8meter / 11.8meter / Customized
Màu sắc	White / Blue / Green / Red / Customized
Wave Spacing	210mm
Chiều cao sóng	24mm
Lớp	One layer / Two layers / Three layers







Tính năng

• Chống ăn mòn

• ZhongXingCheng PVC plastic roofing sheet in the long term against acid, alkali, salt and other corrosive chemicals. Experiments prove that: In the salt, alkali and 60% following a 24-hour soaking in acid, no chemical reaction. Very suitable for acid rainprone areas and coastal use, the effect was particularly significant.

• Không thấm nước

• ZhongXingCheng PVC plastic roofing sheet's surface materials is co-extruded in ultra-weather surface layer resin to ensure the durability of products (for 15 years in quality assurance).

• Fire Resistance

• ZhongXingCheng PVC plastic roofing sheet is a flame retardant materials, through the national fire authority of the department according to GB8624-2006 standards for testing, fire safety performance \geq B1 grade.

• Cách nhiệt

• ZhongXingCheng PVC plastic roofing sheet's thermal conductivity coefficient is 0.325w/mk, clay tile is about 1 / 310, cement tile 1 / 5, 0.5mm thick color steel tile 1 / 2000. Therefore, without considering the case of insulation layer increases, the PVC plastic roofing sheet can still achieve the best thermal insulation properties.

• Sound Insulation

• The tests prove that: in suffering heavy rain, high winds the impact of outside noise, ZhongXingCheng PVC plastic roofing sheet has a good absorption of the noise effect, noise down 30dB than color steel tile.

