

# Product show



1. Một loạt các nguyên liệu thô của một tỷ lệ trộn nhất định, vào phễu



2. Các nguyên liệu thô hỗn hợp là pref -ormed và làm nóng để trở thành gạch phẳng



3. Sau đó thông qua áp suất khuôn, làm dẻo khuôn, làm mát, thông qua máy kéo được giới thiệu từ từ



4. Để đạt được độ dài của nhu cầu khách hàng cắt. sau khi nhân tạo ra









Purplish Red



Brick Red



Sky Blue

















Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				



# Accessories









# Certificate



Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm <sup>3</sup>	---	1.170	---
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Falling ball impact	J/kg	---	---	Confirmed
8	Heat resistance	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
9	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
10	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
11	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
12	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
13	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
14	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
15	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
16	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
17	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
18	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
19	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
20	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural modulus	MPa	≥1.0	1.1	Pass
7	Density	g/cm <sup>3</sup>	---	1.170	---
8	Heat resistance	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
9	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
10	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
11	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
12	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
13	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
14	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
15	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
16	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
17	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
18	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
19	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
20	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass



# Our Factory







# Our Customer





# Packaging



## FAQ

- \* **Bạn là nhà sản xuất hay thương nhân?**
- \* **Vâng, chúng tôi là nhà sản xuất thực sự, có rất nhiều hình ảnh trong giới thiệu công ty của chúng tôi. nếu bạn cần sản phẩm đặc biệt khác, chúng tôi sẽ cố gắng hết sức để giúp bạn, vì vậy chúng tôi có thể xây dựng mối quan hệ kinh doanh lâu dài.**
- \* **Tôi có thể đặt hàng sản phẩm với hồ sơ tôi muốn không?**
- \* **Tất nhiên bạn có thể, chúng tôi cũng sẽ sản xuất các sản phẩm theo yêu cầu chi tiết của bạn.**
- \* **Bạn có thể đặt thương hiệu của công ty tôi trên sản phẩm của bạn không?**



**\* Có, chúng tôi chấp nhận dịch vụ OEM & ODM. Nhưng chúng tôi cần một số thông tin về công ty của bạn.**

**\* Làm thế nào để cài đặt tấm lợp?**

**\* Vui lòng liên hệ với nhân viên dịch vụ của chúng tôi, chúng tôi có video cài đặt cho bạn.**

**\* Bạn có thể cung cấp mẫu để tôi mở thị trường và thử nghiệm không chất lượng?**

**\* Có, chúng tôi có thể. Chúng tôi có thể cung cấp các mẫu miễn phí cho bạn, Bạn có thể trả chi phí vận chuyển không? Vui lòng liên hệ với nhân viên dịch vụ của chúng tôi.**

**\* Điều khoản thương mại của bạn là gì?**

**\* Thanh toán: T/T 30% trước, số dư trước khi giao hàng.**

**• Thời gian sản xuất: Trong vòng 7 ngày làm việc sau khi đặt cọc 30%**

**• Cảng vận chuyển FOB: Phạt Sơn, Quảng Châu, Thâm Quyến**