

Product show

□□□□ □□ **ZXC FRP** □□□□□□ □□ □□□□□ □□□□:

[illegible]

□□□□□□ □□□□□□ □□□:□□□:

[illegible]

□□□□ □□□□:

[illegible]

በጣም በጣም FRP በጣም በጣም ስለ 130 በጣም በጣም በጣም በጣም ስለ 80 በጣም በጣም በጣም በጣም በጣም በጣም በጣም .በጣም በጣም በጣም በጣም በጣም በጣም በጣም በጣም FRP በጣም በጣም በጣም በጣም.

□□□□□□ □□□□□□ □□□□□□ □□□□□□ :

10. 1990 年 10 月 1 日，某公司（以下简称 A 公司）与 B 公司签订了一份买卖合同，约定 A 公司于 1990 年 10 月 10 日交付 B 公司一批货物，B 公司于 1990 年 10 月 15 日支付货款。A 公司于 1990 年 10 月 10 日交付了货物，但 B 公司未按约定支付货款。A 公司于 1990 年 10 月 20 日向 B 公司催款，B 公司未予理睬。A 公司于 1990 年 10 月 25 日向人民法院提起诉讼，请求判令 B 公司支付货款。B 公司辩称，A 公司交付的货物质量不合格，故拒绝支付货款。A 公司辩称，B 公司所称货物质量不合格系其自行检验所致，与 A 公司无关。人民法院经审理后认为，A 公司交付的货物质量符合合同约定，B 公司应当支付货款。遂判令 B 公司于 1990 年 11 月 10 日前支付货款。B 公司不服一审判决，向上一级人民法院提起上诉。上一级人民法院经审理后认为，一审判决认定事实清楚，适用法律正确，遂驳回上诉，维持原判。

[illegible]



ZXC Roof Tile Industry

Reliable quality and worry-free after-sales

FRP LIGHTING ROOF TILE



***10-year
warranty***

CUSTOMER CASE SHOW

Has more than ten years of production experience



厚度:	1.0 mm 2.8 - mm
宽度:	1130/ 930/ 900/ 840 mm
长度:	可定制长度
表面处理:	镀锌 铝 不锈钢 铜
定制服务:	可定制
定制服务 内容:	可定制长度 可定制宽度 可定制厚度 可定制表面处理 可定制颜色 可定制形状 可定制尺寸 可定制重量 可定制数量 可定制包装 可定制运输 可定制安装 可定制维护 可定制其他

A variety of colors, can build different architectural styles

More colors can be customized



light yellow



blue



grass green



Beige

PRODUCT DISPLAY

Authentic product photography highlights the quality of details



CUSTOMER CASE SHOW

More than ten years of production experience



APPLICABLE SCENE DISPLAY

scope of application

~



planting shed

Rainproof, constant temperature
moisturizing space, transparent



roof

Good light transmission
performance, no rain leakage



Villa shed

Bright colors, more class



Recreation area

Color unevenness due to weathering

SIX REASONS “ TO CHOOSE US

Iron tiles can be directly covered



*sound
insulation*

*Anti
-corrosion*

insulation

*High
temperature
resistance*

*anti
-stress*



“ SIX PROPERTIES ”

Good quality and low price. Quality assurance, trustworthy



01 High temperature resistance, frost crack resistance

The product is a solid molecular material, and the operating temperature is -40°-120°



02 Strong bearing capacity, more impact resistance

Add high quality glass fiber



03 Iron tiles can be directly covered

Exclusive research and development technology, more cost-saving.



04 Impact resistance

Shock resistant, not easy to break



05 Good flame retardant performance

Maintain stable performance in the temperature range of -40° - 120° without softening



Our Factory

Zhongxingcheng New Material Co., Ltd. 本公司 設 於 廣東 省 佛 山 市 南 海 區 . 本 公 司 經 營 各 種 新 型 材 料 如 聚 丙 烯 酸 板 材 ASA 聚 丙 烯 酸 板 材 APVC 聚 丙 烯 酸 板 材 PVC 聚 丙 烯 酸 板 材 PVC 聚 丙 烯 酸 板 材 PVC 聚 丙 烯 酸 板 材 FRP 等 材 料 .



FACTORY REAL SHOT DISPLAY

Professional production to do every step



Sampling and testing each batch of products to ensure quality

X



DISPLAY

CUSTOM PROCESS

Easy shopping, quality assurance,
after-sales rest assured



— 01 —

ONLINE CONSULTATION

Provide professional product
consultation



— 02 —

PROVIDE PRICING

Provide reasonable price for
product performance



— 03 —

PREPAID CUSTOMIZATION

Deposit in advance according
to different proportions





—04—

ORDER PRODUCTION

Professional and rapid production
of multiple production lines

—05—

AFTER DELIVERY

Intimate and assured after-sales
service



Exhibition



Certificate

Security sense of authoritative testing

Multiple quality inspection and testing
to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification



Packaging



FAQ

* 00000 00 0000 000 00

0000 000 0000 000 00000 000 000. 000000 00000 00 00000 00 000000 00000 00000000 000000 000 0000 *
.000000 000000 000000 00000 0000 00 00000 000 000000000 000000 000000 0000000

000000 0000000 00 0000 00000 0000000 000 0000000 00*

.00000000000 000000000 000000 0000000000 0000000 000000 0000000 00000 000000 0000000*

000000000 000 0000000 0000000000 000000000 000 000000 00 *

.000000 000 0000000000 000 000 000000 0000000 .00000000 00000000 000000 000000 0000 0000 000 0000 *

□□□□□□□□ □□□□ □□□□□ □□□□□ *

. 00 0000000 000000 000000 000000 000000 000000 000000 0000*

[illegible]

. 00000 000000 000000 0000000 0000 0000000 000000 000 000000 00 000 000000 000000 000000 000000 000000 0000 *

□□□ □□□□□ □□□□□□□ □□□□□ □□ □□ *

□□□□ *: T/T 30% .□□□□ □□ □□□□□ □□□□□

□30 □□□□ □□ □□ □□□ 7 □□□□ □□ :□□□□□□ □□□□ •

□□□□□ □□□□□□□□□ □□□□□ :□□□ □□□□□ □□□□□ •