

Product show



1. A variety of raw materials by a certain percentage mixing, into the hopper



2. The mixed raw materials are pre-formed and heated to become flat tiles



3. Then through the mold pressure, elastic the molding, cooling, through the traction machine slowly introduced



4. To achieve the length of customer needs. after artificial out

اسم المنتج	Spanish Style ASA Roof Tile
ماركة	ZXC
مكان المنشأ	Foshan city, Guangdong province, China (Mainland)
مادة	Acrylonitrile Styrene acrylate copolymer بـ Polyvinyl كلوريد Calcium powder, other chemical materials
يضمن	سنة 25
شهادة	ISO9001 / SGS / CE
أقل كمية ممكن طلبها	100 square meter
موعد التسليم	1x20GP for 6 days, 1x40GP for 7 days
قدرة العرض	We have 8 produce lines, about 13500 square meter every day
شروط الدفع	T/T , firstly pay 30% deposit, before loading container pay rest of payment L/C ,
شحن	Full Container Load (FCL) Service, We do it by myself. Less than Container Load (LCL) Service, We find our agents to do it.
طرد	Pallet or PE bag
ميناء	Guangzhou / Shenzhen / Foshan
تطبيق	Villa roofing, House roofing, Garden, Grange, Container house, Flat to Slope Project, Etc

رقم الموديل	#1050-160-30
يكتب	Spanish Style
العرض الكلي	1050mm
Effective Width	960mm
سماكة	2.3mm / 2.5mm / 2.8mm / 3.0mm

طول	يجب أن يكون مضاعفات الجزء
اللون	Orange / Red / Grey / Sky blue / Dark green
Wave Spacing	160mm
ارتفاع الموجة	30mm
Section Length	219mm

بنية

Surface: Imported ASA raw materials from the world's top 500 GE company, Super weather resistance, truly 10 years don't have color fading. The standard is that the thickness of the surface reaches 0.15mm, We can reach 0.15-0.18mm.

Medium: The material is Polyvinyl و كلوريد Calcium powder, the proportion is 1:1. This is the best ratio after many trials. This ratio guarantees the strength and toughness of the product.

Bottom: The important material also is Polyvinyl و كلوريد Calcium powder, but add other chemical materials. We are make the same color as the surface color and white color. Gloss of products is best in the industry.

ميزة

- (طويلة الأمد اللون (في الأقل 10 أعوام
- The product features ultra durability in natural environment. Even under tough conditions of exposure to UV, high temperature and freezing coldness, it still keeps stable color.
- **Excllent Anti-corrosion performance**
- Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc. Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.
- **Good Waterproofing Performance**
- Synthetic Resin Tile selects highly weater-resistant resin, which is dense and absorbing no water, with no pore penetration problem. The product is 45% wider than traditional tiles with less roof contact, so synthetic resin, s waterproof performance has greatly increased than traditional البلاط.
- **Strong Fire Resistance**
- Belonging flame retardant material, with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.
- **Excellent Heat Insulating Property**
- The heat conductivity coefficient is 0.325w/m.k, about 1/300 of clay tile ,1/50 of cement tile, and 1/2000 of thick color steel tile. Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.
- **Good sound insulation**
- Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.





Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the back surface.	Confirmed	Pass
2	Width deviation	mm	±0.5	0.2	Pass
3	Thickness deviation	mm	±0.02	0.015	Pass
4	Density	g/cm ³	1.170	1.170	Pass
5	Tensile strength	MPa	≥1.0	1.15	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Holding full impact	kJ/m ²	—	—	Confirmed
8	Char temperature	°C	—	—	Confirmed
9	Flammability (UL94)	—	—	—	Confirmed
10	Flammability (UL94)	—	—	—	Confirmed
11	Flammability (UL94)	—	—	—	Confirmed
12	Flammability (UL94)	—	—	—	Confirmed
13	Flammability (UL94)	—	—	—	Confirmed
14	Flammability (UL94)	—	—	—	Confirmed
15	Flammability (UL94)	—	—	—	Confirmed
16	Flammability (UL94)	—	—	—	Confirmed
17	Flammability (UL94)	—	—	—	Confirmed
18	Flammability (UL94)	—	—	—	Confirmed
19	Flammability (UL94)	—	—	—	Confirmed
20	Flammability (UL94)	—	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.10	0.08	Pass
3	Tensile strength	MPa	≥1.0	1.15	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.15	Pass
6	Flexural modulus	MPa	≥1.0	1.15	Pass
7	Density	g/cm ³	1.170	1.170	Pass
8	Heat resistance	°C	—	—	Confirmed
9	Heat resistance	°C	—	—	Confirmed
10	Heat resistance	°C	—	—	Confirmed
11	Heat resistance	°C	—	—	Confirmed
12	Heat resistance	°C	—	—	Confirmed
13	Heat resistance	°C	—	—	Confirmed
14	Heat resistance	°C	—	—	Confirmed
15	Heat resistance	°C	—	—	Confirmed
16	Heat resistance	°C	—	—	Confirmed
17	Heat resistance	°C	—	—	Confirmed
18	Heat resistance	°C	—	—	Confirmed
19	Heat resistance	°C	—	—	Confirmed
20	Heat resistance	°C	—	—	Confirmed



Our Factory





Our Customer



Packaging



FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

لكننا نحتاج إلى بعض المعلومات حول شركتك OEM & ODM. نعم ، نحن نقبل خدمة *

كيفية تثبيت ورقة التسقيف؟*

يرجى الاتصال بموظفي الخدمة لدينا ، لدينا فيديو التثبيت لك*

هل يمكنك تقديم عينات لي لفتح السوق والاختبار ؟؟؟؟*

نعم ، يمكننا. يمكننا تقديم عينات مجانية لك ، هل يمكنك دفع تكلفة الشحن؟ يرجى الاتصال بموظفي الخدمة* لدينا.

ما هو مدة التجارة الخاصة بك؟*

مقدما ، الرصيد قبل الشحن % 30 T/T: الدفع *

• مهلة الإنتاج: في غضون 7 أيام عمل بعد إيداع 30 %

• ميناء الشحن FOB: Foshan ، Guangzhou ، Shenzhen