

Product show



1. Una variedad de materias primas por un cierto porcentaje de mezcla, en la tolva



2. Las materias primas mixtas son preferidas. -
ormado y calentado para convertirse en tejas planas



3. Luego, a través de la presión del molde, se aplica plástico al moldeado, se enfría y se introduce lentamente a través de la máquina de tracción.



4. Para lograr la duración de las necesidades del cliente. cortar. después de salida artificial







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm ³	—	1.170	—
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥2.0	3.1	Pass
7	Holding full impact	kJ/m ²	—	—	Confirmed
8	Char temperature	°C	—	—	Confirmed
9	Flammability (UL94)	—	—	—	Confirmed
10	Flammability (UL94)	—	—	—	Confirmed
11	Flammability (UL94)	—	—	—	Confirmed
12	Flammability (UL94)	—	—	—	Confirmed
13	Flammability (UL94)	—	—	—	Confirmed
14	Flammability (UL94)	—	—	—	Confirmed
15	Flammability (UL94)	—	—	—	Confirmed
16	Flammability (UL94)	—	—	—	Confirmed
17	Flammability (UL94)	—	—	—	Confirmed
18	Flammability (UL94)	—	—	—	Confirmed
19	Flammability (UL94)	—	—	—	Confirmed
20	Flammability (UL94)	—	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥2.0	3.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural modulus	MPa	≥1.0	1.1	Pass
7	Density	g/cm ³	—	1.170	—
8	Heat stability	°C	—	—	Confirmed
9	Heat stability	°C	—	—	Confirmed
10	Heat stability	°C	—	—	Confirmed
11	Heat stability	°C	—	—	Confirmed
12	Heat stability	°C	—	—	Confirmed
13	Heat stability	°C	—	—	Confirmed
14	Heat stability	°C	—	—	Confirmed
15	Heat stability	°C	—	—	Confirmed
16	Heat stability	°C	—	—	Confirmed
17	Heat stability	°C	—	—	Confirmed
18	Heat stability	°C	—	—	Confirmed
19	Heat stability	°C	—	—	Confirmed
20	Heat stability	°C	—	—	Confirmed



Our Factory





Our Customer



Packaging



FAQ

* ¿Es usted fabricante o comerciante?

* Sí, somos fabricantes reales, Hay muchas imágenes en la introducción de nuestra empresa. Si necesita otro producto especial, haremos todo lo posible para ayudarlo, de modo que podamos construir una relación comercial a largo plazo.

* ¿Puedo pedir el producto con el que quiero perfilar?

* Por supuesto que puede, también produciremos los productos de acuerdo con sus solicitudes detalladas.

- * **¿Pueden poner la marca de mi empresa en sus productos?**
- * **Sí, aceptamos servicios OEM y ODM, pero necesitamos información sobre su empresa.**
- * **¿Cómo instalar la lámina para techos?**
- * **Comuníquese con nuestro personal de servicio, tenemos un video de instalación para usted.**
- * **¿Pueden proporcionarme muestras para abrir el mercado y probar? ¿calidad?**
- * **Sí, podemos. Podemos proporcionarle muestras gratuitas. ¿Podría pagar el costo de envío? Comuníquese con nuestro personal de servicio.**
- * **¿Cuál es su término comercial?**
- * **Pago: T/T 30% por adelantado, saldo antes del envío.**
- **Plazo de entrega de producción: dentro de 7 días hábiles después del depósito del 30%**
- **Puerto de envío FOB: Foshan, Guangzhou, Shenzhen**