

Product show

Diseño: estilo español.
Duración del color: 10 años sin decoloración.
Longitud: personalizado
Espesor: 1,8 mm, 2,0 mm, 2,2 mm, 2,5 mm, 2,8 mm, 3,0 mm
Ancho total: 1130 mm
Ancho efectivo: 1000/1050 mm
Espaciado entre correas: 660 mm
Capas: 3 capas
Superficie: en relieve/superficie lisa



Carrying capacity



Flame retardant



Not Conduct Electricity



Corrosion Resistance



White



Green



Blue



Yellow

More Types

1130 corrugaetd sheets



1130 trapezoidal sheets



900 high wave



980 high wave



PVC accessories



ZXC New Material Technology Co., Ltd. Nuestros productos incluyen láminas de PVC, tejas de resina sintética ASA, tejas de FRP, canaletas, láminas para techos de upvc, etc. Si su pedido coincide S nuestros detalles de tamaño de stock, podemos acelerar el tiempo de entrega. Bienvenido Contáctenos Personalizado.

Our Factory



Engineering case



Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	---	The color of tile should be uniform. There should be no stains, cracks or visible impurities on the surface. Edge of the tile should be clean without dust. Weathering should be less, and hydrolysis rate, low.	Confirmed	Pass
2	Walk resistance	mm	≤ 10	8	Pass
3	Thickness deviation	mm	± 0.2	0.12	Pass
4	Skewness	mm/m ²	---	0.08	---
5	Slip resistance	MPa	≥ 0.20	0.21	Pass
6	Expansion of brick	%	≤ 0.20	0.12	Pass
7	Waterfall test impact (kg/m ²)	---	No significant cracks or marks after impact test.	Confirmed	Pass
8	Acid resistance (HCl, H ₂ SO ₄ , H ₂ O ₂)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
9	Alkali resistance (NaOH, NH ₃ ·H ₂ O)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
10	Water absorption (20°C)	mm	≤ 1.0	0.8	Pass
11	Change index	%	≤ 0.10	0.08	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	---	The surface should be smooth with uniform coloration and no visible cracks, pits, marks, stains, or other defects.	Confirmed	Pass
2	Surface layer thickness	mm	≥ 0.15	0.18	Pass
3	Tensile strength	MPa	≥ 2.0	2.8	Pass
4	Bonding strength	%	≥ 20	40	Pass
5	Flexural strength	MPa	≥ 10	15	Pass
6	Flexural ductility modulus	MPa	≥ 1000	1200	Pass
7	Density	g/cm ³	≥ 2.30	2.35	Pass
8	Water absorption (20°C)	%	≤ 1.0	0.8	Pass
9	Change index	%	≤ 0.10	0.08	Pass
10	Waterfall test impact (kg/m ²)	---	No significant cracks or marks after impact test.	Confirmed	Pass
11	Acid resistance (HCl, H ₂ SO ₄ , H ₂ O ₂)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
12	Alkali resistance (NaOH, NH ₃ ·H ₂ O)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
13	Water absorption (20°C)	mm	≤ 1.0	0.8	Pass
14	Change index	%	≤ 0.10	0.08	Pass
15	Waterfall test impact (kg/m ²)	---	No significant cracks or marks after impact test.	Confirmed	Pass
16	Acid resistance (HCl, H ₂ SO ₄ , H ₂ O ₂)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
17	Alkali resistance (NaOH, NH ₃ ·H ₂ O)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
18	Water absorption (20°C)	mm	≤ 1.0	0.8	Pass
19	Change index	%	≤ 0.10	0.08	Pass



Exhibition



Packaging



FAQ

*** ¿Es usted fabricante o comerciante?**

* Sí, somos fabricantes reales, hay muchas imágenes en la introducción de nuestra empresa. Si necesita otro producto especial, haremos todo lo posible para ayudarlo, de modo que podamos construir una relación comercial a largo plazo.

***¿Puedo pedir el producto con el que quiero perfilar?**

* Por supuesto que puede, también produciremos los productos de acuerdo con sus solicitudes detalladas.

*** ¿Puede poner la marca de mi empresa en sus productos?**

* Sí, aceptamos el servicio OEM y ODM. Pero necesitamos información sobre su empresa.

***¿Cómo instalar la lámina para techos?**

* Póngase en contacto con nuestro personal de servicio, tenemos un video de instalación para usted.

*** ¿Puede proporcionarme muestras para abrir el mercado y probar la calidad?**

* Sí, podemos. Podemos proporcionarle muestras gratuitas.

*** ¿Podría usted pagar el costo de envío?**

Póngase en contacto con nuestro personal de servicio.

*** ¿Cuál es su término comercial?**

* Pago: T/T 30% por adelantado, saldo antes del envío.

? Plazo de ejecución de producción: dentro de los 7 días hábiles posteriores al depósito del 30%

? Puerto de envío FOB: Foshan, Guangzhou, Shenzhen