

Product show



1. Une variété de matières premières par un certain pourcentage de mélange, dans la trémie



2. Les matières premières mélangées sont préférées -formés et chauffés pour devenir des carreaux plats



3. Ensuite, à travers la pression du moule, le moulage est élastique, refroidissant, à travers la machine de traction introduite lentement



4. Pour atteindre la longueur des besoins des clients couper. après une sortie artificielle







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm ³	---	1.170	---
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Falling ball impact	J/kg	---	---	Confirmed
8	Heat resistance	---	---	---	Confirmed
9	Flammability	---	---	---	Confirmed
10	Flammability	---	---	---	Confirmed
11	Flammability	---	---	---	Confirmed
12	Flammability	---	---	---	Confirmed
13	Flammability	---	---	---	Confirmed
14	Flammability	---	---	---	Confirmed
15	Flammability	---	---	---	Confirmed
16	Flammability	---	---	---	Confirmed
17	Flammability	---	---	---	Confirmed
18	Flammability	---	---	---	Confirmed
19	Flammability	---	---	---	Confirmed
20	Flammability	---	---	---	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural modulus	MPa	≥1.0	1.1	Pass
7	Density	g/cm ³	---	1.170	---
8	Heat resistance	---	---	---	Confirmed
9	Flammability	---	---	---	Confirmed
10	Flammability	---	---	---	Confirmed
11	Flammability	---	---	---	Confirmed
12	Flammability	---	---	---	Confirmed
13	Flammability	---	---	---	Confirmed
14	Flammability	---	---	---	Confirmed
15	Flammability	---	---	---	Confirmed
16	Flammability	---	---	---	Confirmed
17	Flammability	---	---	---	Confirmed
18	Flammability	---	---	---	Confirmed
19	Flammability	---	---	---	Confirmed
20	Flammability	---	---	---	Confirmed



Our Factory





Our Customer



Packaging



FAQ

* **Vous êtes fabricant ou commerçant ?**

* **Oui, nous sommes un vrai fabricant, il y a de nombreuses photos dans la présentation de notre entreprise. Si vous avez besoin d'un autre produit spécial, nous ferons de notre mieux pour vous aider afin que nous puissions établir une relation commerciale à long terme.**

* **Puis-je commander le produit avec lequel je souhaite créer un profil ?**

* **Bien sûr, vous le pouvez, nous fabriquerons également les produits selon vos demandes détaillées.**

- * **Pouvez-vous apposer la marque de mon entreprise sur vos produits ?**
- * **Oui, nous acceptons le service OEM et ODM. Mais nous avons besoin de quelques informations sur votre entreprise.**
- * **Comment poser la tôle de toiture ?**
- * **Veillez contacter notre personnel de service, nous avons une vidéo d'installation pour vous.**
- * **Pouvez-vous me fournir des échantillons pour ouvrir le marché et tester qualité?**
- * **Oui, nous pouvons. Nous pouvons vous fournir des échantillons gratuits, pourriez-vous payer les frais d'expédition? Veuillez contacter notre personnel de service.**
- * **Quelle est votre condition commerciale?**
- * **Paiement : T/T 30 % à l'avance, solde avant expédition.**
- **Délai de production : dans les 7 jours ouvrables après le dépôt de 30 %**
- **Port d'expédition FOB : Foshan, Guangzhou, Shenzhen**