

Product show

Nom du produit □ Fiche de toit PC transparent

Application: les maisons vertes, les puits de lumière et ainsi de suite

Couleur: blanc transparent, bleu, vert

Longueur □ personnalisée

Épaisseur: 1 mm, 1,2 mm, 1,5 mm, 2,0 mm

Largeur globale: 920 mm

Largeur efficace: 840 mm

Espacement de Purlin □ 700 ~ 800 mm

Surface: Surface lisse

Matière première: PC nommé Bayer



Carrying capacity



Flame retardant



Not Conduct Electricity



Corrosion Resistance



White



Green



Blue



Yellow

More Types

1130 corrugaetd sheets



1130 trapezoidal sheets



900 high wave



980 high wave



PVC accessories



ZXC New Material Technology Co., Ltd. Nos produits comprennent des feuilles de PVC, des carreaux de toit en résine synthétique ASA, des carreaux de toiture FRP, des gouttières, des feuilles de toiture UPVC, etc. Si votre commande correspond nos détails de taille de stock, nous pouvons être plus rapides de livraison. Bienvenue contactez-nous personnalisé.

Our Factory



Engineering case



Certificate



Foshan Supervision Testing Centre of Quality and Metrology

Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	---	The color of tile should be uniform. There should be no stains, cracks or visible imperfections on the surface. Edge of the tile should be clean without chipping. Moisture should be low, and hydrolysis no swelling.	Confirmed	Pass
2	Walk resistance	mm	≤ 10	8	Pass
3	Thickness deviation	mm	±0.2	0.12	Pass
4	Density	g/cm ³	---	1.95	---
5	Break strength	N/m ²	≥ 100	150	Pass
6	Expansion of break	%	≤ 10	10	Pass
7	Soaking full impact (1kg/1m)	---	No significant cracks or chips after impact test.	Confirmed	Pass
8	Acid resistance (10% HCl, 30min, 20°C)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
9	Alkali resistance (10% NaOH, 30min, 20°C)	---	No obvious color change or delamination phenomenon.	Confirmed	Pass
10	Water absorption (30min, 20°C)	mm	≤ 10	12	Pass
11	Change index	%	≤ 10	7.5	Pass

Foshan Supervision Testing Centre of Quality and Metrology

Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	---	The surface should be smooth with uniform coloration and no visible cracks, pits, scratches, stains, or other defects.	Confirmed	Pass
2	Surface layer thickness	mm	≥ 0.12	0.18	Pass
3	Soaking strength	N/m ²	≥ 100	120	Pass
4	Soaking water absorption	%	≤ 10	8	Pass
5	Flexural strength	N/m ²	≥ 100	150	Pass
6	Flexural elastic modulus	N/m ²	≥ 10000	10500	Pass
7	Density	g/cm ³	---	1.95	---
8	Water resistance (10% HCl, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
9	Water resistance (10% NaOH, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
10	Water resistance (10% HCl, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
11	Water resistance (10% NaOH, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
12	Water resistance (10% HCl, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
13	Water resistance (10% NaOH, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
14	Water resistance (10% HCl, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass
15	Water resistance (10% NaOH, 30min, 20°C)	---	No obvious color change after 30min.	Confirmed	Pass



Exhibition



Packaging



FAQ

* **Êtes-vous fabricant ou commerçant?**

* Oui, nous sommes un vrai fabricant, il y a beaucoup de photos dans notre entreprise Introduction. Si vous avez besoin d'un autre produit spécial, nous ferons de notre mieux pour vous aider, afin que nous puissions créer une relation commerciale à long terme.

* **Puis-je commander le produit avec je veux profil?**

* Bien sûr, vous pouvez également produire les produits en fonction de vos demandes de détail.

* **Pouvez-vous mettre la marque de mon entreprise sur vos produits?**

* Oui, nous acceptons le service OEM et ODM. Mais nous avons besoin de quelques informations sur votre entreprise.

* **Comment installer la feuille de toiture?**

* Veuillez contacter notre personnel de service, nous avons une vidéo d'installation pour vous.

* **Pouvez-vous me fournir des échantillons pour ouvrir le marché et tester la qualité?**

* Oui, nous pouvons vous fournir des échantillons gratuits.

* **Pourriez-vous payer le coût d'expédition?**

Veuillez contacter notre personnel de service.

* **Quel est votre terme commercial?**

* Paiement: t / t 30% à l'avance, solde avant expédition.

? Délai de production: dans les 7 jours ouvrables après 30% de dépôt

? Port d'expédition FOB: Foshan, Guangzhou, Shenzhen