



Product Name	ZXC round wave and trapezoid PVC roofing sheet in different colors
Marque	Zxc
Place of Origin	Foshan city,Guangdong province,China(Mainland)
Matériel	Polyvinyl chloride,Calcium powder,other chemical materials
Garantie	10 années
Certification	ISO9001 / SGS / CE
Quantité minimum d'achat	300 square meter
Heure de livraison	1x20GP for 6 days,1x40GP for 7 days
Capacité d'approvisionnement	We have 8 produce lines,about 13500 square meter every day
Modalités de paiement	T/T , firstly pay 30% deposit,before loading container pay rest of payment L/C ,
Expédition	Full Container Load (FCL) Service,We do it by myself. Less than Container Load (LCL) Service,We find our agents to do it.
Emballer	Pallet or PE bag
Port	Guangzhou / Shenzhen / Foshan
Application	Factory,Warehouse,Farm,Market,Aisle.Especially in corrosive chemical plants, smelters, ceramic plants, soy sauce factory, chemical plants, printing and dyeing plant, organic solvent factory, acid, alkali and other corrosive plant




Numéro de modèle
Taper

#1130-210-24
Trapezoid type

Overall Width	1130mm
Effective Width	1050mm
Épaisseur	1.3mm / 1.5mm / 1.8mm / 2.0mm / 2.3mm / 2.5mm / 2.8mm / 3.0mm
Longueur	5.8meter / 11.8meter / Customized
Couleur	White / Blue / Green / Red / Customized
Wave Spacing	210mm
Wave Height	24mm
Couche	One layer / Two layers / Three layers







Fonctionnalité

• Anti-corrosion

• ZhongXingCheng PVC plastic roofing sheet in the long term against acid, alkali, salt and other corrosive chemicals. Experiments prove that: In the salt, alkali and 60% following a 24-hour soaking in acid, no chemical reaction. Very suitable for acid rainprone areas and coastal use, the effect was particularly significant.

• Étanche

• ZhongXingCheng PVC plastic roofing sheet's surface materials is co-extruded in ultra-weather surface layer resin to ensure the durability of products (for 15 years in quality assurance).

• Résistance au feu

• ZhongXingCheng PVC plastic roofing sheet is a flame retardant materials, through the national fire authority of the department according to GB8624-2006 standards for testing, fire safety performance \geq B1 grade.

• Isolation thermique

• ZhongXingCheng PVC plastic roofing sheet's thermal conductivity coefficient is 0.325w/mk, clay tile is about 1 / 310, cement tile 1 / 5, 0.5mm thick color steel tile 1 / 2000. Therefore, without considering the case of insulation layer increases, the PVC plastic roofing sheet can still achieve the best thermal insulation properties.

• Insonorisation

• The tests prove that: in suffering heavy rain, high winds the impact of outside noise, ZhongXingCheng PVC plastic roofing sheet has a good absorption of the noise effect, noise down 30dB than color steel tile.

