

Product show



1. Una varietà di materie prime da a una certa percentuale di miscelazione, nella tramoggia



2. Le materie prime miste sono pre -ormed e riscaldato per diventare piastrelle piatte



3. Quindi attraverso la pressione dello stampo, lastico stampaggio, raffreddamento, attraverso la macchina di trazione lentamente introdotta



4. Per raggiungere la lunghezza dei customerneeds tagliato fuori. dopo l'uscita artificiale







Purplish Red



Brick Red



Sky Blue











Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Status
1	Appearance	—	The color of the sheet is uniform. There shall be no bubble, crack or visible impurities on the surface. Edge of the film should be clean without burr. Direction shall be clear, and both sides are mirror.	Confirmed	Pass
2	Width deviation	mm	±3	0	Pass
3	Thickness deviation	mm	±0.2	-0.02	Pass
4	Density	kg/m ³	—	1.193	—
5	Tensile strength	MPa	≥28	33	Pass
6	Elongation at break	%	≥30	31	Pass
7	Rolling full impact (1kg, 2m)	—	No profound scratch or crack after impact test.	Confirmed	Pass
8	Acid resistance (10% H ₂ SO ₄ /24h)	—	No obvious color change or delamination phenomenon.	Confirmed	Pass
9	Alkal resistance (10% NaOH/24h)	—	No obvious color change or delamination phenomenon.	Confirmed	Pass
10	Flame retardancy (UL94V-0)	mm	≤10	12	Pass
11	Change value	%	≤0.2	0.16	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Status
1	Appearance	—	The surface should be smooth with uniform color and texture. No bubbles, cracks, or other defects are allowed.	Confirmed	Pass
2	Surface layer thickness	mm	0.01-0.1	0.08	Pass
3	Tensile strength	MPa	≥20	26	Pass
4	Tensile at break	%	≥20	20	Pass
5	Flexural strength	MPa	≥16	17	Pass
6	Flexural elastic modulus	MPa	≥2200	2620	Pass
7	Impact	kJ/m ²	≥1.5	1.68	Pass
8	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
9	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
10	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
11	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
12	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
13	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
14	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass
15	Heat resistance (100°C, 2h)	—	No obvious color change or delamination after impact test.	Confirmed	Pass



Our Factory



Packaging



FAQ

***Sei produttore o commerciante?**

***Sì, siamo un vero produttore, ci sono molte immagini nella presentazione della nostra compagnia. se hai bisogno di un altro prodotto speciale, faremo del nostro meglio per aiutarti, in modo che possiamo costruire una relazione commerciale a lungo termine.**

***Posso ordinare il prodotto con il mio profilo?**

***Certo che puoi, inoltre produrremo i prodotti in base alle tue richieste di dettaglio.**

***Puoi mettere il marchio della mia azienda sui tuoi prodotti?**

***Sì, accettiamo il servizio OEM e ODM. Ma abbiamo bisogno di alcune informazioni sulla vostra azienda.**

***Come installare la lamiera del tetto?**

***Si prega di contattare il nostro personale di servizio, abbiamo video di installazione per voi.**

***Potete fornire campioni per me per aprire il mercato e testare qualità?**

***Sì, possiamo. Siamo in grado di fornire campioni gratuiti a voi, potrebbe pagare il costo di spedizione? Si prega di contattare il nostro personale di servizio.**

***Qual è il tuo termine commerciale?**

*** Pagamento: T / T 30% in anticipo, saldo prima della spedizione.**

• Tempo di consegna della produzione: entro 7 giorni lavorativi dal deposito del 30%

• Porto di spedizione FOB: Foshan, Guangzhou, Shenzhen

Contact us

 Tel:+86-13702632466

 Fax:0086-757-81848277

 Skype:jimhuang0.0

 Whatsapp:+86 137 0263 2466

 E-mails:sales08rooftile@zxc9999.com



 Add:Xiebian industrial Area,Danzao Town,Nanhai District,
Foshan City,Guangdong Province