

Product show



1. Una varietà di materie prime da a una certa percentuale di miscelazione, nella tramoggia



2. Le materie prime miste sono prefer -formate e riscaldate per diventare piastrelle piane



3. Quindi attraverso la pressione dello stampo, l'elasticità dello stampaggio, il raffreddamento, viene introdotto lentamente attraverso la macchina di trazione



4. Per raggiungere la lunghezza delle esigenze del cliente tagliare. dopo l'uscita artificiale







Purplish Red



Brick Red



Sky Blue




Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Width deviation	mm	±0.5	0.2	Pass
3	Thickness deviation	mm	±0.02	0.015	Pass
4	Density	g/cm ³	1.170	1.170	Pass
5	Tensile strength	MPa	≥1.0	1.15	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Falling ball impact	J/kg	—	—	Confirmed
8	Heat resistance	—	—	—	Confirmed
9	Flammability	—	—	—	Confirmed
10	Flammability	—	—	—	Confirmed
11	Flammability	—	—	—	Confirmed
12	Flammability	—	—	—	Confirmed
13	Flammability	—	—	—	Confirmed
14	Flammability	—	—	—	Confirmed
15	Flammability	—	—	—	Confirmed
16	Flammability	—	—	—	Confirmed
17	Flammability	—	—	—	Confirmed
18	Flammability	—	—	—	Confirmed
19	Flammability	—	—	—	Confirmed
20	Flammability	—	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.10	0.08	Pass
3	Tensile strength	MPa	≥1.0	1.15	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.15	Pass
6	Flexural modulus	MPa	≥1.0	1.15	Pass
7	Density	g/cm ³	1.170	1.170	Pass
8	Heat resistance	—	—	—	Confirmed
9	Flammability	—	—	—	Confirmed
10	Flammability	—	—	—	Confirmed
11	Flammability	—	—	—	Confirmed
12	Flammability	—	—	—	Confirmed
13	Flammability	—	—	—	Confirmed
14	Flammability	—	—	—	Confirmed
15	Flammability	—	—	—	Confirmed
16	Flammability	—	—	—	Confirmed
17	Flammability	—	—	—	Confirmed
18	Flammability	—	—	—	Confirmed
19	Flammability	—	—	—	Confirmed
20	Flammability	—	—	—	Confirmed



Our Factory





Our Customer



Packaging



FAQ

* Sei produttore o commerciante?

* Sì, siamo un vero produttore, ci sono molte immagini nella nostra presentazione aziendale. se hai bisogno di altri prodotti speciali, faremo del nostro meglio per aiutarti, in modo da poter costruire un rapporto commerciale a lungo termine.

* Posso ordinare il prodotto con voglio profilare?

* Certo che puoi, inoltre produrremo i prodotti in base alle tue richieste dettagliate.

* Puoi mettere il marchio della mia azienda sui tuoi prodotti?

*** Sì, accettiamo il servizio OEM e ODM. Ma abbiamo bisogno di alcune informazioni sulla tua azienda.**

*** Come installare la lamiera di copertura?**

*** Contatta il nostro personale di assistenza, abbiamo un video di installazione per te.**

*** Potete fornirmi campioni per aprire il mercato e testarli qualità?**

*** Sì, possiamo. Possiamo fornirti campioni gratuiti. Potresti pagare il costo di spedizione? Contatta il nostro personale di assistenza.**

*** Qual è il tuo termine commerciale?**

*** Pagamento: T/T 30% in anticipo, saldo prima della spedizione.**

• Tempi di produzione: entro 7 giorni lavorativi dopo il deposito del 30%.

• Porto di spedizione FOB: Foshan, Guangzhou, Shenzhen