

Product show

zxc heat resistant corrugated [Custom ASA PVC Roofing Sheet](#)



1. A variety of raw materials by a certain percentage mixing, into the hopper
2. The mixed raw materials are pre-formed and heated to become flat tiles
3. Then through the mold pressure, elastic the molding, cooling, through the traction machine slowly introduced
4. To achieve the length of customer needs cut off. after artificial out





nome del prodotto	Piastrella da tetto ASA stile spagnolo
Marca	Zxc.
Luogo d'origine	Foshan City, Guangdong Provincia, China (Mainland)
Materiale	Acrilnitrile Stirene Acrilato copolimero, cloruro polivinile, Polvere di calcio, altri materiali chimici
Garanzia	25 anni
Certificazione	ISO9001 / SGS / CE
Quantità di ordine minimo	100 metri quadrati
Tempo di consegna	1x20gp per 6 giorni, 1x40gp per 7 giorni
Capacità di fornitura	Abbiamo 8 linee di produzione, circa 13500 metri quadrati ogni giorno
Termini di pagamento	T / T, in primo luogo pagare il deposito del 30%, prima di caricare il container paga il resto del pagamento L/C ,
Spedizione	Servizio di carico del contenitore completo (FCL), lo facciamo da solo. Meno del servizio di carico del contenitore (LCL), troviamo i nostri agenti per farlo.
Pacchetto	Pallet o sacchetto PE
Porta	Guangzhou / Shenzhen / Foshan
Applicazione	Copertura villa, coperture per la casa, giardino, grange, casa portacontainer, Progetto piatto al pendio, ecc

Numero di modello	# 1050-160-30.
Tipo	Stile spagnolo

Larghezza complessiva	1050mm.
Larghezza efficace	960mm.
Spessore	2,3 mm / 2,5 mm / 2,8 mm / 3,0mm
Lunghezza	Must be a multiple of sezione
Colore	Orange / Red / Grey / Sky blue / Dark green/Customized
Spaziatura dell'onda	160mm.
Altezza d'onda	30mm.
Lunghezza della sezione	219mm.
Purlin Spacing	660mm

More Types



Struttura

Surface: Imported ASA raw materials from the world's top 500 GE company, Super weather resistance, truly 10 years don't have color fading. The standard is that the thickness of the surface reaches 0.15mm, We can reach 0.15-0.18mm.

Medium: The material is Polyvinyl chloride and Calcium powder, the proportion is 1:1. This is the best ratio after many trials. This ratio guarantees the strength and toughness of the product.

Bottom: The important material also is Polyvinyl chloride and Calcium powder, but add other chemical materials. We are make the same color as the surface color and white color. Gloss of products is best in the industry.

Caratteristica

• Long-lasting Color (at least 10 years)

• The product features ultra durability in natural environment. Even under tough conditions of exposure to UV, high temperature and freezing coldness, it still keeps stable color.

• Excellent Anti-corrosion performance

• Synthetic Resin Tile can resist longterm acid, alkali and salt corrosion, etc. Tests have proved that there would be no chemical reaction after soaking in salt and alkali and various acid under 60%. It is ideal for application in areas where acid rain is Comune.

• Good Waterproofing Performance

• Synthetic Resin Tile selects highly weater-resistant resin, which is dense and absorbing no water, with no pore penetration problem. The product is 45% wider than traditional tiles with less roof contact, so synthetic resin's waterproof performance has greatly increased than traditional tiles.

• Strong Fire Resistance

• Belonging flame retardant material, with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.

• Excellent Heat Insulating Property

• The heat conductivity coefficient is 0.325w/m.k, about 1/300 of clay tile, 1/50 of cement tile, and 1/2000 of thick color steel tile. Therefore without condidering ading heat-preserving layer, the heat insulation and heat preservation of synthetic resin tile can still be optimized.

• Good sound insulation

• Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.

resin roof tile accessories



▶ Step1



▶ Step2



▶ Step3



▶ Step4



▶ Step5



▶ Step6

Our Factory




Engineering case



Certificate



Packaging



Spessore		2.3mm	2.5mm	2.8mm	3.0mm
Peso (kg/SQM)		4.6	5.0	5.6	6.0
Container Load Capacity	20 GP (21Tons)	4500	4200	3750	3500
	40GP (26 Tons)	5600	5200	4600	4300

Caratteristica:

1. ExcllentAnti corrosivoPrestazione
- 2.GoodImpermeabilePrestazione
- 3.FireResistenza
- 4.Heatisolamento
- 5.Sound ins ulation
6. Weather.soliditàinvecchiamentoresistenza

Pacchetto:Nudoostandardesportarepacchetto

FAQ

*Sei produttore o commerciante?

*Sì, siamo reali ([Produttore di tetti in PVC ASA Cina](#)) Ci sono molte foto nella nostra introduzione della nostra azienda.Se hai bisogno di un altro prodotto speciale, faremo del nostro meglio per aiutarti, quindi possiamo costruire una relazione commerciale a lungo termine.

*Posso ordinare il prodotto con cui voglio profilo?

*Naturalmente puoi, anche produrremo i prodotti in base alle tue richieste di dettaglio.

*Puoi mettere il marchio della mia azienda sui tuoi prodotti?

*Sì, siamo accettati OEM & ODM Service.Mo abbiamo bisogno di informazioni sulla tua azienda.

***Come installare il foglio di copertura?**

*Si prega di contattare il nostro personale di servizio, abbiamo un video di installazione per te.

***Puoi fornire campioni per me per aprire il mercato e testare qualità?**

*Sì, possiamo dobbiamo fornire campioni gratuiti a te, potresti pagare i costi di spedizione? Si prega di contattare il nostro personale di servizio.

***Qual è il tuo termine commerciale?**

* Pagamento: T / T 30% in anticipo, equilibrio prima della spedizione.

- Tempo di consegna della produzione: entro 7 giorni lavorativi dopo il deposito del 30%
- Porta di spedizione FOB: Foshan, Guangzhou, Shenzhen