

Product show



1. A variety of raw materials by a certain percentage mixing, into the hopper



2. The mixed raw materials are pre-formed and heated to become flat tiles



3. Then through the mold pressure, elastic the molding, cooling, through the traction machine slowly introduced



4. To achieve the length of customer needs tagliato fuori. after artificial out

nome del prodotto	Spanish Style ASA Roof Tile
Marca	ZXC
Luogo d'origine	Foshan city, Guangdong province, China (Mainland)
Materiale	Acrylonitrile Styrene acrylate copolymer, Polyvinyl cloruro, Polvere di calcio, other chemical materials
Garanzia	25 anni
Certificazione	ISO9001 / SGS / CE
Quantità di ordine minimo	100 square meter
Tempo di consegna	1x20GP for 6 days, 1x40GP for 7 days
Supply Ability	We have 8 produce lines, about 13500 square meter every day
Termini di pagamento	T/T , firstly pay 30% deposit, before loading container pay rest of payment L/C ,
Spedizione	Full Container Load (FCL) Service, We do it by myself. Less than Container Load (LCL) Service, We find our agents to do it.
Pacchetto	Pallet or PE bag
Porta	Guangzhou / Shenzhen / Foshan
Applicazione	Villa roofing, House roofing, Garden, Grange, Container house, Flat to Slope Project, Etc
Numero di modello	#1050-160-30
Tipo	Spanish Style
Larghezza complessiva	1050mm
Effective Width	960mm

Spessore	2.3mm / 2.5mm / 2.8mm / 3.0mm
Lunghezza	Must be a multiple of sezione
Colore	Orange / Red / Grey / Sky blue / Dark green
Wave Spacing	160mm
Altezza d'onda	30 mm
Section Length	219mm

Struttura

Surface: Imported ASA raw materials from the world's top 500 GE company, Super weather resistance, truly 10 years don't have color fading. The standard is that the thickness of the surface reaches 0.15mm, We can reach 0.15-0.18mm.

Medium: The material is Polyvinyl chloride and Powder of calcium, the proportion is 1:1. This is the best ratio after many trials. This ratio guarantees the strength and toughness of the product.

Bottom: The important material also is Polyvinyl chloride and Powder of calcium, but add other chemical materials. We are make the same color as the surface color and white color. Gloss of products is best in the industry.

Caratteristica

- **Di lunga durata Colore (A meno 10 anni)**
 - The product features ultra durability in natural environment. Even under tough conditions of exposure to UV, high temperature and freezing coldness, it still keeps stable color.
- **Excellent Anti-corrosion performance**
 - Synthetic Resin Tile can resist longterm acid, alkali and salt corrosion, etc. Tests have proved that there would be no chemical reaction after soaking in salt and alkali and various acid under 60%. It is ideal for application in areas where acid rain is common.
- **Good Waterproofing Performance**
 - Synthetic Resin Tile selects highly water-resistant resin, which is dense and absorbing no water, with no pore penetration problem. The product is 45% wider than traditional tiles with less roof contact, so synthetic resin's waterproof performance has greatly increased than traditional tiles.
- **Strong Fire Resistance**
 - Belonging flame retardant material, with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.
- **Excellent Heat Insulating Property**
 - The heat conductivity coefficient is 0.325w/m.k, about 1/300 of clay tile, 1/50 of cement tile, and 1/2000 of thick color steel tile. Therefore without considering adding heat-preserving layer, the heat insulation and heat preservation of synthetic resin tile can still be optimized.
- **Good sound insulation**
 - Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.





Purplish Red



Brick Red



Sky Blue


















Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	---	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass	
2	Wall thickness	mm	0.5	0.5	Pass	
3	Thickness deviation	mm	±0.02	±0.02	Pass	
4	Density	g/cm ³	1.170	1.170	Pass	
5	Tensile strength	MPa	≥2.0	2.0	Pass	
6	Elongation at break	%	≥2.0	2.0	Pass	
7	Holding full impact	kJ/m ²	---	---	Confirmed	Pass
8	Char-impact	---	---	---	Confirmed	Pass
9	Char-impact (150°C)	---	---	---	Confirmed	Pass
10	Char-impact (200°C)	---	---	---	Confirmed	Pass
11	Flaming impact	---	---	---	Confirmed	Pass
12	Flaming impact (150°C)	---	---	---	Confirmed	Pass
13	Flaming impact (200°C)	---	---	---	Confirmed	Pass
14	Impact strength	kJ/m ²	---	---	---	---
15	Impact strength (150°C)	---	---	---	---	---
16	Impact strength (200°C)	---	---	---	---	---

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	---	The surface should be smooth and uniform. There should be no bubbles, cracks, visible impurities, or other defects.	Confirmed	Pass	
2	Surface roughness	mm	0.15	0.15	Pass	
3	Tensile strength	MPa	≥2.0	2.0	Pass	
4	Elongation at break	%	≥2.0	2.0	Pass	
5	Flexural strength	MPa	≥0.8	0.8	Pass	
6	Flexural deflection	MPa	≥0.8	0.8	Pass	
7	Density	g/cm ³	1.170	1.170	Pass	
8	Heat stability	h	50	50	Pass	
9	Heat stability (150°C)	---	---	---	Confirmed	Pass
10	Heat stability (200°C)	---	---	---	Confirmed	Pass
11	Heat stability (250°C)	---	---	---	Confirmed	Pass
12	Heat stability (300°C)	---	---	---	Confirmed	Pass
13	Heat stability (350°C)	---	---	---	Confirmed	Pass
14	Heat stability (400°C)	---	---	---	Confirmed	Pass
15	Heat stability (450°C)	---	---	---	Confirmed	Pass
16	Heat stability (500°C)	---	---	---	Confirmed	Pass
17	Heat stability (550°C)	---	---	---	Confirmed	Pass
18	Heat stability (600°C)	---	---	---	Confirmed	Pass
19	Heat stability (650°C)	---	---	---	Confirmed	Pass
20	Heat stability (700°C)	---	---	---	Confirmed	Pass
21	Heat stability (750°C)	---	---	---	Confirmed	Pass
22	Heat stability (800°C)	---	---	---	Confirmed	Pass
23	Heat stability (850°C)	---	---	---	Confirmed	Pass
24	Heat stability (900°C)	---	---	---	Confirmed	Pass
25	Heat stability (950°C)	---	---	---	Confirmed	Pass
26	Heat stability (1000°C)	---	---	---	Confirmed	Pass



Our Factory





Our Customer



Packaging



FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

*** Sì, accettiamo il servizio OEM e ODM. Ma abbiamo bisogno di alcune informazioni sulla tua azienda.**

***Come installare il foglio di copertura?**

***Si prega di contattare il nostro personale di servizio, abbiamo un video di installazione per te.**

***Puoi fornirmi campioni per aprire il mercato e testare qualità?**

***Sì, possiamo. Possiamo fornirti campioni gratuiti, potresti pagare i costi di spedizione? Per favore contatta il nostro personale di servizio.**

***Qual è il tuo termine commerciale?**

*** Pagamento: t/t 30% in anticipo, saldo prima della spedizione.**

• Tempo di consegna della produzione: entro 7 giorni lavorativi dal 30% di deposito

• Porta di spedizione FOB: Foshan, Guangzhou, Shenzhen