

Product show

00 000000 **ZXC** 0**RP** 00000000 0000 00000000 00000000:

[illegible]

□□□□ □□ □□□□:

[illegible]

□□□□ □□□□:

[illegible][illegible][illegible][illegible]

ZXC ٲٲٲ ٲٲ ,ٲٲٲ ٲٲٲٲٲٲٲ ٲٲ ٲٲٲٲ ٲٲٲٲٲ ,ٲٲٲ ٲٲٲٲ ٲٲٲٲٲٲ ٲٲٲٲ ٲٲٲٲ ٲٲٲ ٲ ٲٲٲ ٲٲٲٲ ٲٲ ٲٲٲٲٲ ٲٲ ٲٲٲٲٲ ٲٲٲٲ ٲٲٲٲ!



ZXC Roof Tile Industry

Reliable quality and worry-free after-sales

FRP LIGHTING ROOF TILE



***10-year
warranty***



Complete specifications



Support customization



Adequate inventory



product available

פרטים כלליים		פרטים טכניים	
frp-01		פרטים טכניים	
6000 מ"מ		11800 מ"מ	
930 מ"מ		840 מ"מ	
840 מ"מ		660 מ"מ	
1.0±0.1 מ"מ		1.2±0.1 מ"מ	
1.5±0.1 מ"מ		2.0±0.1 מ"מ	
1.7±0.1 מ"מ/ס"מ		2.1±0.1 מ"מ/ס"מ	
2.6±0.1 מ"מ/ס"מ		3.0±0.1 מ"מ/ס"מ	
SQ.M./20 FCL (21 ימים)		SQ.M./40 FCL (26 ימים)	
12000 מ"מ		15000 מ"מ	
10000 מ"מ		12300 מ"מ	
8000 מ"מ		10000 מ"מ	
7000 מ"מ		8600 מ"מ	

גיליון גלי ספק סין ללמוד יותר [frp](#) נקישה

CUSTOMER CASE SHOW

Has more than ten years of production experience



厚度:	1.0 mm 2.8 mm
宽度:	1130/ 930/ 900/ 840 mm
长度:	标准长度 定制
表面处理:	镀锌 铝 铝合金 不锈钢
应用:	建筑
应用:	屋顶 墙面 隔断 装饰 工业 农业 交通 市政 环保 能源 水利 电力 机械 化工 医药 食品 包装 印刷 纺织 造纸 木材 塑料 橡胶 陶瓷 玻璃 金属 其他

A variety of colors, can build different architectural styles

More colors can be customized



light yellow



blue




grass green



Beige

PRODUCT DISPLAY

Authentic product photography highlights the quality of details



CUSTOMER CASE SHOW

More than ten years of production experience



APPLICABLE SCENE DISPLAY

scope of application

~



planting shed

Rainproof, constant temperature
moisturizing space, transparent



roof

Good light transmission
performance, no rain leakage



Villa shed

Bright colors, more class



Recreation area

Color unevenness due to weathering

SIX REASONS “ TO CHOOSE US

Iron tiles can be directly covered




*sound
insulation*

*Anti
-corrosion*

insulation

*High
temperature
resistance*

*anti
-stress*



“ SIX PROPERTIES ”

Good quality and low price. Quality assurance, trustworthy



01 High temperature resistance, frost crack resistance

The product is a solid molecular material, and the operating temperature is -40°-120°



02 Strong bearing capacity, more impact resistance

Add high quality glass fiber



03 Iron tiles can be directly covered

Exclusive research and development technology, more cost-saving.



04 Impact resistance

Shock resistant, not easy to break



05 Good flame retardant performance


Maintain stable performance in the temperature range of -40° - 120° without softening

[illegible]



FACTORY REAL SHOT DISPLAY

Professional production to do every step



Sampling and testing each batch of products to ensure quality

X



DISPLAY

CUSTOM PROCESS

Easy shopping, quality assurance,
after-sales rest assured



— 01 —

ONLINE CONSULTATION

Provide professional product
consultation



— 02 —

PROVIDE PRICING

Provide reasonable price for
product performance



— 03 —

PREPAID CUSTOMIZATION

Deposit in advance according
to different proportions





— **04** —

ORDER PRODUCTION

Professional and rapid production
of multiple production lines

— **05** —

AFTER DELIVERY

Intimate and assured after-sales
service



Exhibition



Certificate

Security sense of authoritative testing

Multiple quality inspection and testing
to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification



Packaging



FAQ

*? 0000 00 0000 000 000
00000 0000 00000 ,000 00000 0000 0000 000 00 .0000 00000 00000 00000 0000 00 ,00000 0000 00000 ,00*
.0000 00000 00000 00000 00000 00000 00000 0000 000 ,00 00000 000 00000000

?பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள்*
 .பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள்*
 .பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள் பெரியவர்கள்*

?□□□ □□□□□□□□ □□ □□□□ □□□□□□ □□ □□□□□□ □□□□ □□□□ □□□□ □□□□*

1. OEM & ODM.

2. MOQ

3. Lead time

4. Payment

5. Shipping

6. Terms

7. T/T 30%

8. 30%

9. FOB