



zxc roofing tile industry

After sales less is really good

Ten years of slow fading, **30** years of warranty



GOOD CHOICE

Our advantage



Intimate service, strong product supply capacity



product available



A variety of styles and specifications sufficient stock



Support customization



Specifications and sizes can be consulted with customer service in detail, and quotations can be customized



Worry-free after sales



Manufacturers wholesale quality assurance, affordable prices, worry-free after-sales

SOURCE MANUFACTURER

>



THE TROUBLES OF TRADITIONAL ROOF TILES

#

other products

×



severely faded

Wind and sun soften and fade



There is a gap

Uneven with gaps, leaking rain



uneven color

Weathered uneven color
phenomenon



Fragile

Fragile and complicated
to install

our products ✓

Ten years of slow fading, 30 years of warranty



Uniform color, durable and not easy to fade
Good quality, durable and bright.




high toughness



Strong pressure resistance

Effective insulation



good sound insulatio



thermal and acoustic insulation high-quality
Good sound insulation effect in case of external noise



preservative
Anti-acid and alkali



flame retardant performance
b1 class fire performance

PRODUCT PARAMETERS

#

>



thickness: 1.0mm-3.0mm
width: 1130/980/900/840/1080mm
length: customizable
waveform: big hang, small wave
type: asa plastic roofing tile
Be applicable: Factory buildings, ware houses, markets, residences, market roads, canopies, chemically corrosive factories

A variety of colors, optional to build different architectural styles

More colors can be customized



<Mlight yellow>



<dark blue>



<grass green>



<Beige>

CUSTOMER CASE SHOW





Factory renovation



Our Factory

Zhongxingcheng New Material Co., Ltd 專業生產 各種規格 鋼板 鋼管 , 鋼絲 鋼絲網 鋼絲繩 , 鋼絲繩 鋼絲繩 鋼絲繩 鋼絲繩 鋼絲繩 ASA, 鋼絲繩 鋼絲繩 鋼絲繩 鋼絲繩 APVC, 鋼絲繩 PVC 鋼絲繩 , 鋼絲繩 鋼絲繩 PVC, 鋼絲繩

Quality inspection instruments strictly control the quality

Each batch of products has undergone rigorous testing.



Gravity testing



Hardness testing



Tensile force testing



Impact resistance testing

Factory display



In-stock inventory



Own production line



Own production line



Exhibition



Certificate

Official quality inspection, quality assurance

Multiple quality inspection and testing to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification



MA
201812121212

检

佛山市质
Foshan Supervision

No. G14-WT1489

佛山市质量计量监督检测中心

检验报告

报告号: QB-049-02 No. G14-WT1489
 共 2 页, 第 2 页

序号	检测项目	单位	标准要求	检测结果	判定
1	外观	—	表面光滑平整, 厚度均匀, 色泽一致, 无裂纹、缺口、破孔、烧焦、气泡、明显麻点、杂质点	符合	合格
2	密度	g/cm ³	1.45~1.65	1.64	合格
3	弯曲性能	mm	支撑跨度800mm, 载荷40kg, 允许挠度≤50	15	合格
4	冲击性能	—	1kg重钢球, 1.5m自由落体, 冲击试样无碎裂, 试样经冲击试验后不得产生贯穿的孔穴或裂纹	符合	合格
5	抗拉强度	%	≥60	63	合格

审核: 王博斌 主检: 陈德聪

全部合格

No. G14-WT1489

中心

共 2 页, 第 1 页

生产日期: —

编号或批号: —

样品编号: —

检测类别: 委托检测

样品数量: 2件

检测日期: 2019年02月24日

检测人: 李东平

0046标准的要素:

二〇一九年四月

佛山市质量计量监督检测中心

主检: 陈德聪

Q: What is your company's main product? A: We are a professional manufacturer of various types of shoes, including men's, women's, and children's shoes. We have a rich experience in shoe production and a complete production line.

Q: Do you have any certifications? A: Yes, we have ISO 9001 and ISO 14001 certifications.

Q: How long has your company been in business? A: Our company has been in business for over 10 years.

Q: What is your company's production capacity? A: Our company has a production capacity of 100,000 pairs of shoes per month.

Q: How do you ensure the quality of your products? A: We have a strict quality control system and a professional quality control team. We ensure that every pair of shoes meets our high standards of quality.

Q: What are your payment terms? A: We accept T/T, L/C, and other payment methods.

Q: How do you handle shipping? A: We have a professional shipping department and can handle all types of shipping.

Q: How long is your lead time? A: Our lead time is 7-10 days.

Q: What are your main markets? A: Our main markets are Europe, America, and Africa.