

Product show



1. Ang iba't ibang mga hilaw na materyales sa pamamagitan ng isang ilang porsyento paghahalo, tohe tipaklong



2. Ang pinaghalong raw na materyales ay pref-normed at pinainit upang maging flat tile



3. Pagkatapos ay sa pamamagitan ng presyon ng hulma, pagkatapos ay ang paghubog, paglamig, sa pamamagitan ng traksyon machine dahan-dahan ipinakilala



4. Upang makamit ang haba ng customerneeds putulin. pagkatapos ng artipisyal na out







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	—	The color of the sheet is uniform. There shall be no bubble, crack or visible impurities on the surface. Each of the 10 sheets to check within this condition should be used, and each also on average.	Conformed	Pass
2	Width deviation	mm	±3	0	Pass
3	Thickness deviation	mm	±0.2	-0.02	Pass
4	Density	g/m ²	—	1750	—
5	Tensile strength	MPa	≥28	35	Pass
6	Elongation at break	%	≥30	33	Pass
7	Falling ball impact (1kg, 1m)	—	No profuse cracks or cracks after impact test.	Conformed	Pass
8	Acid resistance (10% H ₂ SO ₄ /24h)	—	No obvious color change or delamination phenomenon.	Conformed	Pass
9	Alkal resistance (10% NaOH/24h)	—	No obvious color change or delamination phenomenon.	Conformed	Pass
10	Flame retardancy (UL94V-0)	mm	≤10	12	Pass
11	Change value	%	≤10	7.50	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Remark
1	Appearance	—	The surface should be smooth with uniform color and texture. There shall be no bubble, crack, visible impurities, or staining.	Conformed	Pass
2	Surface layer thickness	mm	0.05-0.15	0.10	Pass
3	Tensile strength	MPa	≥20	20	Pass
4	Tensile at break	%	≥20	20	Pass
5	Flexural strength	MPa	≥16	15	Pass
6	Flexural elastic modulus	MPa	≥2200	2620	Pass
7	Impact	kJ/m ²	≥1.5	1.58	Pass
8	Water absorption (24h, 23±2°C)	%	≤0.5	0.0	Pass
9	Water vapor permeability (23±2°C, 50% RH)	g/m ² ·24h	≤0.1	0.0	Pass
10	Heat sealability (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass
11	Heat seal strength (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass
12	Heat seal strength (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass
13	Heat seal strength (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass
14	Heat seal strength (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass
15	Heat seal strength (120°C, 10s)	—	The joint strength is not less than 80% of the original strength.	Conformed	Pass



Our Factory



Our Customer



Packaging



FAQ

***Ikaw ba ay tagagawa o negosyante?**

***Oo, kami ay tunay na gumagawa, Maraming mga larawan sa pagpapakilala ng aming kumpanya.kung kailangan mo ng iba pang mga espesyal na produkto, gagawin namin ang aming makakaya upang matulungan ka, upang makagawa kami ng isang pangmatagalang relasyon sa negosyo.**

***Maaari ba akong mag-order ng produkto sa gusto kong profile?**

***Siyempre maaari mong, din kami ay gumawa ng mga produkto ayon sa iyong mga kahilingan sa detalye.**

***Maaari mo bang ilagay ang tatak ng aking kumpanya sa iyong mga produkto?**

***Oo, kami ay tumatanggap ng OEM & ODM service. But kailangan namin ng ilang impormasyon tungkol sa iyong kumpanya.**

***Paano mag-install ng roofing sheet?**

***Mangyaring makipag-ugnay sa aming kawani ng serbisyo, mayroon kaming pag-install ng video para sa iyo.**

***Maaari kang magbigay ng mga halimbawa para sa akin upang buksan ang merkado at pagsubok kalidad?**

***Oo, maaari namin. Maaari kaming magbigay ng mga libreng sample sa iyo, Maaari ba kayong magbayad ng gastos sa pagpapadala? Mangyaring makipag-ugnay sa aming kawani ng serbisyo.**

***Ano ang iyong termino sa kalakalan?**

*** Pagbabayad: T / T 30% nang maaga, balanse bago ipadala.**

• Oras ng Lead ng Produksyon: Sa loob ng 7 araw ng trabaho pagkatapos ng 30% na deposito

• FOB Shipping Port: Foshan, Guangzhou, Shenzhen

Contact us

 Tel:+86-13702632466

 Fax:0086-757-81848277

 Skype:jimhuang0.0

 Whatsapp:+86 137 0263 2466

 E-mails:sales08rooftile@zxc9999.com



 Add:Xiebian industrial Area,Danzao Town,Nanhai District,
Foshan City,Guangdong Province