Our Foshan ZXC New Material Technology Co., Ltd. is UPVC PVC Gutters Manufacturer provide customized and OEM services.

PVC gutter taking place of the metal gutter, anti-acid and alkali-resistant, nice out-looking and durable. Easy installation with high efficiency and low labor cost.

We the blue pvc rain water gutter bears extremely strong toughness, comparing with the common gutter, it solves the issues of short life span, transportation, being easily damage during the installation etc.

Warranty	More than 5 years	
After-sale Service	Online technical support	
Project Solution Capability	NONE	
Application	Villa/ Hydroponics	
Design Style	Contemporary	
Place of Origin	Guangdong, China	
Brand Name	ZXC	
Product name	PVC Rainwater Gutter	
Material	PVC	
Key Word	Gutter	
Size	Customizable	
Usage	Roof Drain	
Warranty	More than 5 years	
Common size	14cmx 16cm.18cmx 20cm.25cmx 28CM	
Performance	Acid and alkali resistant	

QUALITY RAIN GUTTER

Made of PVC, resistant to pressure and corrosion, durable

Feeding gutter | planting gutter | incubation gutter | rain gutter





PRODUCT FEATURE DISPLAY



new raw material

Using high-quality raw materials, no recycled materials, green environmental protection, long life



Thickened load-bearing PVC material has strong bending resistance and impact toughness





Product Information



*The length of this section is one meter, the longest can be six meters

Product name	Specification	Accessories
	Base width 14cm, height 16cm, face width 19cm, thickness 2.5mm	
niddle gutter Base width 18cm, height 20cm, face width 25cm, thickness 2.8mm		Drain seal drain seal flush joint corne
	Base width 25cm, height 28cm, face width 35cm, thickness 3.8mm	

Click <u>PVC rain water gutter supplier china</u> to learn more





RAIN GUTTER ACCESSORIES

Complete accessories, selected quality



Advantage



Trust comes from quality

GLASS GLUE PORTABLE INSTALLATION

Quick installation in 2 minutes Compared with traditional fixed rivets, it saves time, effort and worry





INSTALLATION INSTRUCTIONS



1. When installing the rain gutter, the bottom supporting frame shouldbe made of steel frame, and the material should be sufficiently strong. The bottom frame should be in a straight line and there should be a supporting place every 1.5-1.8 meters. The two sides of the rain guttermust be protected by iron frames.

2. The two ends of the connection part of the rain gutter or the connectionport should be supported by the supporting bracket respectively.

3. Do not open holes in any part of the rain gutter for drainage withoutauthorization. This will affect the service life of the rain gutter, and special drainage fittings and water pipes are required to connect to the downpipe.

4. It must be pre-drilled during installation, and the diameter of the drilledhole should be 50% larger than the diameter of the screw, which is reserved for thermal expansion and contraction.

5. The outside temperature changes greatly. In order to prevent thermalexpansion and contraction, it is recommended that the installation of the entire gutter should not exceed 18 meters. If it is to be exceeded, segmental installation and segmental drainage must be carried out.





Real case, real power

Selected engineering cases









Trust comes from quality

THE PRODUCT IS VERY VERSATILE

Versatility leads to creative life











AUTHORITATIVE ORGANIZATION INSPECTION

There is a certificate and guarantee and only with strength can you rest assured





1.Q: What is your product line?

A: We specialize in PVC trunking, PVC pipe, PPR pipe and fittings.

2.Q: Are you a manufacturer?

A: Yes, We are a factory located in Foshan City, Nanhai District, Danzao Town, Hengjiang New Road. More than 10 years of industry experience.

3.Q: If I want to get a quote, what information should I notify?

Answer:

- (1) Product size (width x height x length, thickness).
- (2) Color.
- (3) Quantity.

4.Q: Can we print our logo or company name on your product or packaging?

A: Yes, you can.

5.Q: What is the payment term?

A: We accept T/T or L/C, as well as the top 30% deposits of T/T, Western Uion,

6.Q: Is the sample free?

A: We can send samples within 5 days, but the shipping cost needs to be paid by you. When we have a formal order, its cost will rebound.

7.Q: How to control your quality?

A: We strictly select high quality raw materials and regularly check quality control during production.

8.Q: How long should your delivery date be?

A: Usually 15 days after receiving the deposit, it also depends on your product and quantity.