

# Product show



1. Uma variedade de matérias-primas por um certa porcentagem de mistura, dentro da tremonha



2. As matérias-primas mistas são preferidas -ormed e aquecido para se tornar telhas planas



3. Em seguida, através da pressão do molde, lasque a moldagem, esfrie, através da máquina de tração introduzida lentamente



4. Para atingir o comprimento das necessidades do cliente cortar. depois da saída artificial







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

# Accessories







# Certificate



Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm <sup>3</sup>	—	1.170	—
5	Tensile strength	MPa	≥1.0	1.1	Pass
6	Elongation at break	%	≥1.0	1.1	Pass
7	Falling ball impact	J/kg	—	—	Confirmed
8	Heat resistance	—	—	—	Confirmed
9	Flammability	—	—	—	Confirmed
10	Flame retardancy	—	—	—	Confirmed
11	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed
12	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed
13	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed

Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks, visible impurities, or other defects.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥1.0	1.1	Pass
4	Elongation at break	%	≥1.0	1.1	Pass
5	Flexural strength	MPa	≥1.0	1.1	Pass
6	Flexural ductility	MPa	≥1.0	1.1	Pass
7	Density	g/cm <sup>3</sup>	—	1.170	—
8	Heat resistance	—	—	—	Confirmed
9	Flammability	—	—	—	Confirmed
10	Flame retardancy	—	—	—	Confirmed
11	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed
12	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed
13	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed



# Our Factory





# Our Customer



# Packaging



## FAQ

\* **Você é fabricante ou comerciante?**

\* **Sim, somos fabricantes reais, há muitas fotos na introdução da nossa empresa. se você precisar de outro produto especial, faremos o possível para ajudá-lo, para que possamos construir um relacionamento comercial de longo prazo.**

\* **Posso encomendar o produto com o perfil que desejo?**

\* **Claro que você pode, também produziremos os produtos de acordo com suas solicitações detalhadas.**

**\* Você pode colocar a marca da minha empresa em seus produtos?**

**\* Sim, aceitamos serviço de OEM e ODM. Mas precisamos de algumas informações sobre sua empresa.**

**\* Como instalar a telha de cobertura?**

**\* Entre em contato com nossa equipe de serviço, temos vídeo de instalação para você.**

**\* Você pode fornecer amostras para eu abrir o mercado e testar qualidade?**

**\* Sim, nós podemos. Nós podemos fornecer amostras grátis para você, você poderia pagar o custo de envio? Entre em contato com nossa equipe de atendimento.**

**\* Qual é o seu termo comercial?**

**\* Pagamento: T/T 30% adiantado, saldo antes do envio.**

**• Prazo de entrega da produção: Dentro de 7 dias úteis após o depósito de 30%**

**• FOB Porto de embarque: Foshan, Guangzhou, Shenzhen**