

Product show



1. A variety of raw materials by a certain percentage mixing, into the hopper



2. The mixed raw materials are pre-formed and heated to become flat tiles



3. Then through the mold pressure, plastic molding, cooling, through the traction machine slowly introduced



4. To achieve the length of customer needs, cut after artificial out

Nome do Produto	Spanish Style ASA Roof Tile
Marca	ZXC
Lugar de origem	Foshan city, Guangdong province, China (Mainland)
Material	Acrylonitrile Styrene acrylate copolymer, Assim, Polyvinyl cloreto, Assim, Calcium powder, other chemical materials
Garantia	25 anos
Certificação	ISO9001 / SGS / CE
Minimum Order Quantity	100 square meter
Tempo de entrega	1x20GP for 6 days, 1x40GP for 7 days
capacidade de fornecimento	We have 8 produce lines, about 13500 square meter every day
Termos de pagamento	T/T , firstly pay 30% deposit, before loading container pay rest of payment L/C ,
Envio	Full Container Load (FCL) Service, We do it by myself. Less than Container Load (LCL) Service, We find our agents to do it.
Pacote	Pallet or PE bag
Porta	Guangzhou / Shenzhen / Foshan
Inscrição	Villa roofing, House roofing, Garden, Grange, Container house, Flat to Slope Project, Etc
Model Number	#1050-160-30
Tipo	Spanish Style
Largura total	1050mm

Effective Width	960mm
Espessura	2.3mm / 2.5mm / 2.8mm / 3.0mm
Comprimento	Deve ser um múltiplo de seção
Cor	Orange / Red / Grey / Sky blue / Dark green
Wave Spacing	160mm
Altura da onda	30mm
Section Length	219mm

Estrutura

Surface:Imported ASA raw materials from the world's top 500 GE company,Super weather resistance, truly 10 years don,t have color fading.The standard is that the thickness of the surface reaches 0.15mm,We can reach 0.15-0.18mm.

Medium:The material is Polyvinyl cloreto e Calcium powder,the proportion is 1:1.This is the best ratio after many trials.This ratio guarantees the strength and toughness of the product.

Bottom:The important material also is Polyvinyl cloreto e Calcium powder,but add other chemical materials.We are make the same color as the surface color and white color.Gloss of products is best in the industry.

Característica

- **Duradouro Cor (no ao menos 10 anos)**
 - The product features ultra durability in natural environment.Even under tough conditions of exposure to UV,high temperature and freezing coldness,it still keeps stable color.
- **Excllent Anti-corrosion performance**
 - Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc.Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is common.
- **Good Waterproofing Performance**
 - Synthetic Resin Tile selects highly weater-resistant resin,which is dense and absorbing no water,with no pore penetration problem.The product is 45% wider than traditional tiles with less roof contact,so synthetic resin,s waterproof performance has greatly increased than traditional azulejos.
- **Strong Fire Resistance**
 - Belonging flame retardant material,with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.
- **Excellent Heat Insulating Property**
 - The heat conductivity coefficient is 0.325w/m.k,about 1/300 of clay tile ,1/50 of cement tile,and 1/2000 of thick color steel tile.Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.
- **Good sound insulation**
 - Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.





Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass
2	Wall thickness	mm	0.2	0.2	Pass
3	Thickness deviation	mm	±0.02	±0.02	Pass
4	Density	g/cm ³	---	1.15	---
5	Tensile strength	MPa	≥2.0	3.0	Pass
6	Elongation at break	%	≥2.0	1.0	Pass
7	Falling ball impact	J/kg	---	---	Confirmed
8	Heat resistance	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
9	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
10	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
11	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
12	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
13	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
14	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
15	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
16	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
17	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
18	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
19	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
20	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	---	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥2.0	3.0	Pass
4	Elongation at break	%	≥2.0	1.0	Pass
5	Flexural strength	MPa	≥2.0	3.0	Pass
6	Flexural modulus	MPa	≥2.0	3.0	Pass
7	Density	g/cm ³	---	1.15	---
8	Heat resistance	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
9	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
10	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
11	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
12	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
13	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
14	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
15	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
16	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
17	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
18	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
19	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass
20	Flammability	---	The material should change no color after 10h at 120°C.	Confirmed	Pass



Our Factory





Our Customer



Packaging



FAQ

***Are you manufacturer or trader?**

***Yes, we are real manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.**

***Can I order the product with i want to profile?**

***Of course you can, also we will produce the products according to your detail requests.**

***Can you put my company's brand on your products?**

*** Sim, somos aceitados em serviço OEM e ODM. Mas precisamos de algumas informações sobre sua empresa.**

***Como instalar a folha de cobertura?**

***Entre em contato com a equipe de serviço, temos o vídeo de instalação para você.**

***Você pode fornecer amostras para eu abrir o mercado e testar qualidade?**

***Sim, podemos fornecer amostras gratuitas para você, você poderia pagar o custo de envio? Entre em contato com a equipe de serviço.**

***Qual é o seu termo comercial?**

*** Pagamento: T/T 30% de antecedência, saldo antes da remessa.**

• PRODUÇÃO LEVIDO DO LEVO: Dentro de 7 dias úteis após 30% de depósito

• Porta de remessa FOB: Foshan, Guangzhou, Shenzhen