

Product show

FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。

FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。

FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。

FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。

FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。

ZXC 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。FRP 鋼筋管具有優良的耐腐蝕性能，適用於各種腐蝕性介質的輸送和儲存。



ZXC Roof Tile Industry

Reliable quality and worry-free after-sales

FRP LIGHTING ROOF TILE



***10-year
warranty***

CUSTOMER CASE SHOW

Has more than ten years of production experience



厚度:	1.0mm-2.8mm
规格:	1130/ 930/ 900/ 840mm
材质:	铝/ 钢
表面处理:	阳极氧化/ 镀锌/ 喷漆
用途:	建筑幕墙/ 装饰板/ 隔断板
产地:	中国
联系方式:	13800000000 0000 0000 0000000000 000 0000 000000 000000 000000000000 000000000000 000

A variety of colors, can build different architectural styles

More colors can be customized



light yellow



blue




grass green



Beige

PRODUCT DISPLAY

Authentic product photography highlights the quality of details



CUSTOMER CASE SHOW

More than ten years of production experience



APPLICABLE SCENE DISPLAY

scope of application

~



planting shed

Rainproof, constant temperature
moisturizing space, transparent



roof

Good light transmission
performance, no rain leakage



Villa shed

Bright colors, more class



Recreation area

Color unevenness due to weathering

SIX REASONS “ TO CHOOSE US

Iron tiles can be directly covered




*sound
insulation*

*Anti
-corrosion*

insulation

*High
temperature
resistance*

*anti
-stress*



“ SIX PROPERTIES ”

Good quality and low price. Quality assurance, trustworthy



01 High temperature resistance, frost crack resistance

The product is a solid molecular material, and the operating temperature is -40°-120°



02 Strong bearing capacity, more impact resistance

Add high quality glass fiber



03 Iron tiles can be directly covered

Exclusive research and development technology, more cost-saving.



04 Impact resistance

Shock resistant, not easy to break



05 Good flame retardant performance

Maintain stable performance in the temperature range of -40° - 120° without softening



06

Good light transmission

The light is astigmatism, the light is soft, and the light transmittance is high.

Our Factory

Zhongxingcheng New Material Co., Ltd. 佛山市南海区 Foshan City, Nanhai District China

ASA,


APVC, PVC, PVC,

PVC, FRP, PVC, PC



FACTORY REAL SHOT DISPLAY

Professional production to do every step



Sampling and testing each batch of products to ensure quality

X



DISPLAY

CUSTOM PROCESS

Easy shopping, quality assurance,
after-sales rest assured



— 01 —

ONLINE CONSULTATION

Provide professional product
consultation



— 02 —

PROVIDE PRICING

Provide reasonable price for
product performance



— 03 —

PREPAID CUSTOMIZATION

Deposit in advance according
to different proportions





—04—

ORDER PRODUCTION

Professional and rapid production
of multiple production lines

—05—

AFTER DELIVERY

Intimate and assured after-sales
service



Exhibition



Certificate

Security sense of authoritative testing

Multiple quality inspection and testing
to ensure good quality.



IOS9000 certified



China Metrology Certification



CAL certification



Packaging



FAQ

- [illegible]

* 請提供貴公司之詳細資料，包括公司名稱、地址、電話、傳真、電子郵件、網址等？

* 請提供貴公司之產品目錄，OEM 或 ODM 產品，請提供產品之詳細資料，包括產品名稱、規格、價格、數量、交付時間等？

* 請提供貴公司之產品之詳細資料？

* 請提供貴公司之產品之詳細資料，包括產品名稱、規格、價格、數量、交付時間等？

* 請提供貴公司之產品之詳細資料，包括產品名稱、規格、價格、數量、交付時間等？

* 請提供貴公司之產品之詳細資料，包括產品名稱、規格、價格、數量、交付時間等？
請提供貴公司之產品之詳細資料，包括產品名稱、規格、價格、數量、交付時間等？

* 請提供貴公司之產品之詳細資料？

* 請提供貴公司之產品之詳細資料：T/T 請提供貴公司 30% 請提供貴公司之詳細資料

• 請提供貴公司之產品之詳細資料：請提供 7 請提供貴公司之詳細資料 30%

• FOB Shipping Port: 請提供 請提供貴公司 請提供貴公司