[illegible]	[illegible] [illegible] PVC [illegible] 10 [illegible]
[illegible]	ZXC
[illegible]	[illegible] ([illegible])
[illegible]	[illegible],[illegible],[illegible]
[illegible]	10 [illegible]
[illegible]	ISO9001 / [illegible] / CE
[illegible]	300 [illegible]
[illegible]	1x20GP [illegible] 6 [illegible], 1x40GP [illegible] 7 [illegible]
[illegible]	[illegible] 8 [illegible] 13,500 [illegible]
[illegible]	T/T [illegible] 30% [illegible] [illegible]/C,
[illegible]	[illegible] Full Container Load (FCL) [illegible] [illegible] (LCL) [illegible]
[illegible]	[illegible] PE
[illegible]	[illegible] / [illegible] / [illegible]
[illegible]	[illegible], [illegible], [illegible], [illegible], [illegible] [illegible], [illegible], [illegible], [illegible], [illegible], [illegible], [illegible], [illegible], [illegible]



[illegible]	#1130-210-24
[illegible]	[illegible]
[illegible]	1130[illegible]
[illegible]	1,050[illegible]

□□□□□□□	1.3 □□. / 1.5 □□. / 1.8 □□. / 2.0 □□. / 2.3 □□. / 2.5 □□. / 2.8 □□. / 3.0 □□.
□□□□□□□	5.8 □□□□ / 11.8 □□□□ / □□□□□□□□□□□
□□	□□□ / □□□□□□□ / □□□□□ / □□□ / □□□□□□□□
□□□□□□□□□□□□□□□□	210□□
□□□□□□□□□□□□□□□	24□□
□□□□	□□□□□□□□□□/□□□□□□□□/□□□□□□□□







[illegible]

• [illegible]

• [illegible] PVC ZhongXingCheng [illegible] [illegible] [illegible]
[illegible] [illegible] [illegible]: [illegible] 60%
[illegible] 24 [illegible] [illegible]
[illegible]
[illegible]

• [illegible]

• [illegible] PVC ZhongXingCheng
[illegible]
[illegible] ([illegible] 15 [illegible])

• [illegible]

• [illegible] ZhongXingCheng [illegible]
[illegible] GB8624-2006 [illegible]
[illegible] ≥ [illegible] B1

• [illegible]

• [illegible] PVC ZhongXingCheng [illegible]
0.325w/mk [illegible] 1/310 [illegible] 1/5 [illegible] 0.5
[illegible]. 1/2000 [illegible] [illegible]
[illegible]

• [illegible]

• [illegible]: [illegible] [illegible]

□□□□□□□□□□□□□□□□□□ ZhongXingCheng □□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□ 30dB
□□□□□□□□□□□□□□□□