

# Product show



1. 紅色的ASA原料顆粒

2. 紅色的ASA原料顆粒 - 正在被加工成片



3. 正在被加工成片的ASA原料

4. 堆疊好的ASA原料片

ASA原料	ASA原料
ASA原料	ASA原料
ASA原料	ASA原料 (ASA原料)
ASA原料	ASA原料 ASA原料 ASA原料, ASA原料, ASA原料
ASA原料	25
ASA原料	ISO9001/ASA原料/CE
ASA原料	100
ASA原料	1x20GP ASA原料 6 1x40GP ASA原料 7
ASA原料	ASA原料 8 ASA原料 13500 ASA原料
ASA原料	T / T ASA原料 30% ASA原料
ASA原料	ASA原料 Full Container Load (FCL) ASA原料 (LCL) ASA原料
ASA原料	ASA原料 PE
ASA原料	ASA原料/ASA原料/ASA原料
ASA原料	ASA原料, ASA原料, ASA原料, Grange, ASA原料, ASA原料 Flat to Slope
ASA原料	#1050-160-30
ASA原料	ASA原料
ASA原料	1050
ASA原料	960







Purplish Red



Brick Red



Sky Blue

















Black



Dark Green



Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

# Accessories









# Certificate



Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass	
2	Width deviation	mm	±0.5	0.2	Pass	
3	Thickness deviation	mm	±0.02	0.015	Pass	
4	Density	g/cm <sup>3</sup>	1.170	1.170	Pass	
5	Tensile strength	MPa	≥1.0	1.15	Pass	
6	Elongation at break	%	≥1.0	1.5	Pass	
7	Holding full impact	kJ/m <sup>2</sup>	—	—	Confirmed	Pass
8	Char temperature	°C	—	—	Confirmed	Pass
9	Flammability	—	—	—	Confirmed	Pass
10	Flame spread	—	—	—	Confirmed	Pass
11	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass
12	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology  
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks, visible impurities, or other defects.	Confirmed	Pass	
2	Surface roughness	mm	0.15	0.15	Pass	
3	Tensile strength	MPa	≥1.0	1.15	Pass	
4	Elongation at break	%	≥1.0	1.5	Pass	
5	Flexural strength	MPa	≥1.0	1.15	Pass	
6	Flexural modulus	MPa	≥1.0	1.15	Pass	
7	Density	g/cm <sup>3</sup>	1.170	1.170	Pass	
8	Heat stability	—	—	—	Confirmed	Pass
9	Char temperature	°C	—	—	Confirmed	Pass
10	Flammability	—	—	—	Confirmed	Pass
11	Flame spread	—	—	—	Confirmed	Pass
12	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass
13	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass
14	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass
15	Impact strength	kJ/m <sup>2</sup>	—	—	Confirmed	Pass



# Our Factory







# Our Customer









\* 請提供詳細的技術規格書 **OEM** 或 **ODM** 服務，並說明相關的專利權、商標權、版權等法律問題。

\* 請提供詳細的生產計劃表？

\* 請提供詳細的品質管理系統 (QMS) 認證，如 ISO 9001 等。

\* 請提供詳細的研發團隊背景，包括成員的學歷、經驗、專長等？

\* 請提供詳細的財務狀況，包括最近三年的財務報表、資產負債表、現金流量表等，並說明公司的盈利能力和風險。

\* 請提供詳細的市場推廣計劃？

\* 請提供詳細的付款條件：**T / T** 或 **30%** 預付。

• 請提供詳細的交貨日期：**7** 天內交貨，**30%** 預付。

• **FOB Shipping Port:** 請提供詳細的港口名稱及地址。