Product show

1. [illegible] [illegible]	2. [illegible] - [illegible]
3. [illegible] [illegible]	4. [illegible] [illegible]

[illegible]	[illegible] ASA [illegible]
[illegible]	[illegible]
[illegible]	[illegible] [illegible] [illegible] ([illegible])
[illegible]	[illegible] [illegible] [illegible] [illegible], [illegible] , [illegible] ,[illegible]
[illegible]	25 [illegible]
[illegible]	ISO9001/[illegible]/CE
[illegible]	100 [illegible].[illegible]
[illegible]	1x20GP [illegible] 6 [illegible] 1x40GP [illegible] 7 [illegible]
[illegible]	[illegible] 8 [illegible] 13500 [illegible]
[illegible]	T / T [illegible] 30% [illegible] [illegible]/[illegible] ,
[illegible]	[illegible] Full Container Load (FCL) [illegible] [illegible] (LCL) [illegible]
[illegible]	[illegible] PE
[illegible]	[illegible]/[illegible]/[illegible]
[illegible]	[illegible], [illegible], [illegible], [illegible], [illegible], [illegible] [illegible]

[illegible]	#1050-160-30
[illegible]	[illegible]
[illegible]	1050[illegible]
[illegible]	960[illegible]

[illegible]	2.3[illegible]./2.5[illegible]./2.8[illegible]./3.0[illegible]
[illegible]	[illegible] [illegible] [illegible]
[illegible]	[illegible] / [illegible] / [illegible] / [illegible] / [illegible]
[illegible]	160[illegible]
[illegible]	30[illegible]
[illegible]	219[illegible]

[illegible]

[illegible]: [illegible] [illegible] [illegible] ASA [illegible] 500 GE [illegible] 10 [illegible] 0.15 [illegible]. [illegible] 0.15-0.18 [illegible].

[illegible]:[illegible] 1:1 [illegible]

[illegible]: [illegible]

[illegible]

- [illegible] [illegible] ([illegible] 10 [illegible])
- [illegible]

- [illegible]
- [illegible] 60% [illegible].

- [illegible]
- [illegible] 45% [illegible].

- [illegible]
- [illegible] ≥ B1 [illegible] GBB8624-2006

- [illegible]
- [illegible] 0.325w/m.k [illegible] 1/300 [illegible] 1/50 [illegible] 1/2000 [illegible]

- [illegible]
- [illegible]







Purplish Red | Brick Red | Sky Blue | Black | Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm－3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excllent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories

Certificate

Our Factory

Our Customer

Packaging

FAQ

* □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□?

* □□□ □□□□□□□□□□□□□□□□□□□□ □□□ . □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□ □□ □□ □□□□□□□□□□□□□□□□□□□□

* □□□?

* □□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□ □□

* □□?

* [illegible] [illegible] OEM [illegible] ODM [illegible]

* [illegible]?

* [illegible] [illegible].

* [illegible] [illegible]?

* [illegible] [illegible] [illegible] [illegible]
[illegible]

* [illegible]?

* [illegible]: T / T [illegible] 30% [illegible]

• [illegible]: [illegible] 7 [illegible] 30%

• FOB Shipping Port: [illegible] [illegible] [illegible]