


Product show

ZXC ASA [Synthetic Resin Roof Tile](#) Wholesales, If your order matches our stock size details, we can faster delivery time.



1. A variety of raw materials by a certain percentage mixing, into the hopper
2. The mixed raw materials are pre-formed and heated to become flat tiles
3. Then through the mold pressure, plastic molding, cooling, through the traction machine slowly introduced
4. To achieve the length of customer needs cut off. after artificial out





产品名称	Spanish Style ASA Roof Tile
型号	ZXC
产地	Foshan city,Guangdong province,China(Mainland)
材料	Acrylonitrile Styrene acrylate copolymer,Polyvinyl chloride, Calcium powder,other chemical materials
使用寿命	25 years
Certification	ISO9001 / SGS / CE
Minimum Order Quantity	100 square meter
交货期	1x20GP for 6 days,1x40GP for 7 days
Supply Ability	We have 8 produce lines,about 13500 square meter every day
付款方式	T/T , firstly pay 30% deposit,before loading container pay rest of payment L/C ,

□□□□□□□□□□	Full Container Load (FCL) Service,We do it by myself. Less than Container Load (LCL) Service,We find our agents to do it.
□□□□□□□□□□	Pallet or PE bag
□□□□□□□	Guangzhou / Shenzhen / Foshan
□□□□□□□□□□	Villa roofing,House roofing,Garden,Grange,Container house, Flat to Slope Project,Etc

Model Number	#1050-160-30
□□□□□	Spanish Style
Overall Width	1050mm
Effective Width	960mm
□□□□□□□	2.3mm / 2.5mm / 2.8mm / 3.0mm
□□□□□□□	Must be a multiple of □□□□
□□	Orange / Red / Grey / Sky blue / Dark green/Customized
Wave Spacing	160mm
Wave Height	30mm
Section Length	219mm
Purlin Spacing	660mm

More Types



□□□□□□□□

Surface:Imported ASA raw materials from the world's top 500 GE company,Super weather resistance, truly 10 years don,t have color fading.The standard is that the thickness of the surface reaches 0.15mm,We can reach 0.15-0.18mm.

Medium:The material is Polyvinyl chloride and Calcium powder,the proportion is 1:1.This is the best ratio after many trials.This ratio guarantees the strength and toughness of the product.

Bottom:The important material also is Polyvinyl chloride and Calcium powder,but add other chemical materials.We are make the same color as the surface color and white color.Gloss of products is best in the industry.

□□□□□□□□

• **Long-lasting Color (at least 10 years)**

• The product features ultra durability in natural environment.Even under tough conditions of exposure to UV,high temperature and freezing coldness,it still keeps stable color.

• **Excllent Anti-corrosion performance**

• Synthetic Resin Tile can resist longterm acid ,alkali and salt corrosion ,etc.Tests have proved that there would be no chemical reaction after soaking in salt and alikali and various acid under 60% .It is ideal for application in areas where acid rain is □□□□□□.

• **Good Waterproofing Performance**

• Synthetic Resin Tile selects highly weater-resistant resin,which is dense and absorbing no water,with no pore penetration problem.The product is 45% wider than traditional tiles with less roof contact,so synthetic resin,s waterproof performance has greatly increased than traditional tiles.

• **Strong Fire Resistance**

• Belonging flame retardant material,with fire resistance \geq B1 as tested by national authoritative departments according to GBB8624-2006 standard.

• **Excellent Heat Insulating Property**

• The heat conductivity coefficient is 0.325w/m.k,about 1/300 of clay tile ,1/50 of cement tile,and 1/2000 of thick color steel tile.Therefore without condidering ading heat-preserving layer ,the heat insulation and heat preservation of synthetic resin tile can still be optimized.

• **Good sound insulation**

• Tests have proved that synthetic resin tiles have excellent noise absorption function when suffered heavy rains and strong winds.

□□□□□□ [ASA PVC Roof Tile Suppliers](#) to know more

resin roof tile accessories



▶ Step1



▶ Step2



▶ Step3



▶ Step4



▶ Step5



▶ Step6

Our Factory




Engineering case



Certificate



Packaging



□□□□□□□□		2.3mm	2.5mm	2.8mm	3.0mm
□□□□□□□□ (kg/SQM)		4.6	5.0	5.6	6.0
Container Load Capacity	20 GP (21Tons)	4500	4200	3750	3500
	40GP (26 Tons)	5600	5200	4600	4300

□□□□□□□□□□:

1. Excellent Anti-corrosion□□□□□□
2. Good□□□□□□□□ □□□□□□
3. Fire□□□□□□□□□□□□
4. Heat insulation
5. Sound insulation
6. Weather fastness, ageing□□□□□□□□□□□□

□□□□□□□□□□: Nude□□□□□□□□□□□□□□□□□□□□□□□□

FAQ

***Are you manufacturer or trader?**

*Yes, we are real Manufacturer, there are many pictures in our company introduction .if you need other special product, we will do our best to help you, so we can build a long-term business relationship.

***Can I order the product with i want to profile?**

*Of course you can, also we will produce the products according to your detail requests.

***Can you put my company's brand on your products?**

*Yes,we are accept OEM&ODM service.But we need some information about your company.

***How to install the roofing sheet?**

*Please contact our service staff, we have installation video for you.

Can you provide samples for me to open the market and test 100000?

*Yes,we can.We can provide free samples to you ,Could you pay the shipping cost?Please contact our service staff.

***What is your trade term?**

* Payment: T/T 30% in advance, balance before shipment.

• Production Lead Time: Within 7 working days after 30% deposit

• FOB Shipping Port: Foshan,Guangzhou,Shenzhen