

Product show



1. 紅瓦

2. 紅瓦 - 切割機



3. 紅瓦

4. 紅瓦







Purplish Red



Brick Red



Sky Blue



Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict	
1	Appearance	—	The color of the sheet is uniform. There should be no bubbles, cracks or visible impurities on the surface. There should be no visible defects on the surface.	Confirmed	Pass	
2	Width deviation	mm	±0.5	0.2	Pass	
3	Thickness deviation	mm	±0.1	0.05	Pass	
4	Density	g/cm ³	1.170	1.170	Pass	
5	Tensile strength	MPa	≥2.0	2.5	Pass	
6	Elongation at break	%	≥2.0	3.0	Pass	
7	Holding full impact	kJ/m ²	—	—	Confirmed	Pass
8	Char-FTIR	—	—	—	Confirmed	Pass
9	Char-FTIR	—	—	—	Confirmed	Pass
10	Char-FTIR	—	—	—	Confirmed	Pass
11	Char-FTIR	—	—	—	Confirmed	Pass
12	Char-FTIR	—	—	—	Confirmed	Pass
13	Char-FTIR	—	—	—	Confirmed	Pass
14	Char-FTIR	—	—	—	Confirmed	Pass
15	Char-FTIR	—	—	—	Confirmed	Pass
16	Char-FTIR	—	—	—	Confirmed	Pass
17	Char-FTIR	—	—	—	Confirmed	Pass
18	Char-FTIR	—	—	—	Confirmed	Pass
19	Char-FTIR	—	—	—	Confirmed	Pass
20	Char-FTIR	—	—	—	Confirmed	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Verdict
1	Appearance	—	The surface should be smooth and uniform. There should be no bubbles, cracks or visible impurities on the surface.	Confirmed	Pass
2	Surface roughness	mm	0.1	0.1	Pass
3	Tensile strength	MPa	≥2.0	2.5	Pass
4	Elongation at break	%	≥2.0	3.0	Pass
5	Flexural strength	MPa	≥2.0	2.5	Pass
6	Flexural deflection	MPa	≥2.0	2.5	Pass
7	Density	g/cm ³	1.170	1.170	Pass
8	Heat stability	h	≥2.0	2.5	Pass
9	Heat stability	h	≥2.0	2.5	Pass
10	Heat stability	h	≥2.0	2.5	Pass
11	Heat stability	h	≥2.0	2.5	Pass
12	Heat stability	h	≥2.0	2.5	Pass
13	Heat stability	h	≥2.0	2.5	Pass
14	Heat stability	h	≥2.0	2.5	Pass
15	Heat stability	h	≥2.0	2.5	Pass
16	Heat stability	h	≥2.0	2.5	Pass
17	Heat stability	h	≥2.0	2.5	Pass
18	Heat stability	h	≥2.0	2.5	Pass
19	Heat stability	h	≥2.0	2.5	Pass
20	Heat stability	h	≥2.0	2.5	Pass



Our Factory





Our Customer



* 請提供詳細的技術規格書 **OEM** 或 **ODM** 服務商名稱及地址，以便我們進行評估。

* 請提供您的公司名稱及地址？

* 請提供您的公司名稱及地址，以便我們進行評估。

* 請提供您的公司名稱及地址，以便我們進行評估？

* 請提供您的公司名稱及地址，以便我們進行評估。請提供您的公司名稱及地址，以便我們進行評估。

* 請提供您的公司名稱及地址？

* 請提供您的公司名稱：**T / T** 服務商名稱 **30%** 服務商名稱

• 請提供您的公司名稱：**7** 服務商名稱 **30%**

• **FOB Shipping Port:** 請提供 服務商名稱 服務商名稱