
Ürün adı	ZXC round wave and trapezoid PVC roofing sheet in different colors			
Marka	ZXC			
Anavatan	Foshan city, Guangdong province, China (Mainland)			
Malzeme	Polyvinyl chloride, Calcium powder, other chemical materials			
Garanti	10 yıl			
Certification	ISO9001 / SGS / CE			
minimum sipariş miktarı	300 square meter			
Teslimat süresi	1x20GP for 6 days,1x40GP for 7 days			
Supply Ability	We have 8 produce lines, about 13500 square meter every day			
Ödeme şartları	$\ensuremath{\text{T/T}}$, firstly pay 30% deposit, before loading container pay rest of payment L/C ,			
Nakliye	Full Container Load (FCL) Service, We do it by myself. Less than Container Load (LCL) Service, We find our agents to do it.			
Paket	Pallet or PE bag			
Liman	Guangzhou / Shenzhen / Foshan			
Factory, Warehouse, Farm, Market, Aisle. Especially in corrosive chemplants, smelters, ceramic plants, soy sauce factory, chemical plants printing and dyeing plant, organic solvent factory, acid, alkali and corrosive plant				



Model numarası #1130-210-24
Tip Trapezoid type
Overall Width 1130mm

Effective Width 1050mm

Kalınlık 1.3mm / 1.5mm / 1.8mm / 2.0mm / 2.3mm / 2.5mm / 2.8mm /

3.0mm


Uzunluk 5.8meter / 11.8meter / Customized


Renk White / Blue / Green / Red / Customized

Wave Spacing 210mm Dalga yüksekliği 24mm

Katman One layer / Two layers / Three layers







Özellik

Anti korozyon

• ZhongXingCheng PVC plastic roofing sheet in the long term against acid, alkali, salt and other corrosive chemicals. Experiments prove that: In the salt, alkali and 60% following a 24-hour soaking in acid, no chemical reaction. Very suitable for acid rainprone areas and coastal use, the effect was particularly significant.

• Su geçirmez

• ZhongXingCheng PVC plastic roofing sheet's surface materials is co-extruded in ultra-weather surface layer resin to ensure the durability of products (for 15 years in quality assurance).

Fire Resistance

• ZhongXingCheng PVC plastic roofing sheet is a flame retardant materials, through the national fire authority of the department according to GB8624-2006 standards for testing, fire safety performance \geq B1 grade.

• Isı yalıtımı

• ZhongXingCheng PVC plastic roofing sheet's thermal conductivity coefficient is 0.325 w/mk, clay tile is about 1 / 310, cement tile 1 / 5, 0.5mm thick color steel tile 1 / 2000. Therefore, without considering the case of insulation layer increases, the PVC plastic roofing sheet can still achieve the best thermal insulation properties.

• Ses yalıtımı

• The tests prove that: in suffering heavy rain, high winds the impact of outside noise, ZhongXingCheng PVC plastic roofing sheet has a good absorption of the noise effect,noise down 30dB than color steel tile.