

Product show



1. Một loạt các nguyên liệu của một tỷ lệ pha trộn nhất định, phểu vào



2. Nguyên liệu hỗn hợp là pref - được nung và nung nóng để trở thành gạch phẳng





3. Sau đó, thông qua áp lực khuôn, lastic đúc, làm mát, thông qua máy kéo từ từ giới thiệu



4. Để đạt được độ dài của các tùy chỉnh cắt. sau khi nhân tạo ra







Purplish Red



Brick Red



Sky Blue









Black



Dark Green

Product name		ASA Synthetic Resin Roof Tile			
Material		ASA(Acrylonitrile Styrene acrylate copolymer)+PVC(Polyvinyl chloride)			
Type		Spanish Style			
Overall Width		1050mm			
Effective Width		960mm			
Thickness		2.3mm—3.0mm			
Length		Customized(According to the size of container)			
Color		Customized			
Purlin Spacing		660mm			
Thickness		2.3mm	2.5mm	2.8mm	3.0mm
Weight (kg/SQM)		4.6	5.0	5.6	6.0
Container Load capacity	20 GP (21 Tons)	4500	4200	3750	3500
	40 GP (26 Tons)	5600	5200	4600	4300
Feature		1.Excellent Anti-corrosion Performance 2.Good Waterproof Performance 3.Fire Resistance 4.Heat insulation 5.Sound insulation 6.Weather fastness,ageing resistance			
Package		Nude or standard export package			

Item No.	Name	Picture	Item No.	Name	Picture
1	ASA Synthetic Resin Tile		7	Main Ridge Tile Head	
2	Main Ridge Tile			Main Ridge Turnup	
3	Tilted Ridge Tile		8	Four-way	
4	Tilted Ridge Tile Head		9	Left / Right Eave Sealing Tile	
	Tilted Ridge Turnup		10	Guide Plate Tile	
5	Modern eave drip tile		11	Vertical Wall Flashing Tile	
	Antique eave drip tile		12	Screw And Hat	
6	Three-way				

Accessories





Certificate



Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Status
1	Appearance	—	The color of the sheet is uniform. There shall be no bubble, void or visible impurities on the surface. Edge of the film should be clean without burr. Direction shall be even, and both sides are straight.	Confirmed	Pass
2	Width deviation	mm	±3	0	Pass
3	Thickness deviation	mm	±0.2	-0.02	Pass
4	Density	g/cm ³	—	1.193	—
5	Tensile strength	MPa	≥28	33	Pass
6	Elongation at break	%	≥30	33	Pass
7	Folding full impact (1kg, 2m)	—	No profuse marks or cracks after impact test.	Confirmed	Pass
8	Acid resistance (10% H ₂ SO ₄ /24h)	—	No obvious color change or delamination phenomenon.	Confirmed	Pass
9	Alkal resistance (10% NaOH/24h)	—	No obvious color change or delamination phenomenon.	Confirmed	Pass
10	Flame retardancy (UL94V-0)	mm	≤10	12	Pass
11	Change value	%	≤10	7.91	Pass

Foshan Supervision Testing Centre of Quality and Metrology
Test Report

No.	Item	Unit	Requirement	Result	Status
1	Appearance	—	The surface should be smooth with uniform color and texture. No bubbles, voids, or other defects are allowed.	Confirmed	Pass
2	Surface layer thickness	mm	0.01-0.1	0.08	Pass
3	Tensile strength	MPa	≥20	26	Pass
4	Tensile at break	%	≥200	200	Pass
5	Flexural strength	MPa	≥16	17	Pass
6	Flexural elastic modulus	MPa	≥2200	2620	Pass
7	Impact	kJ/m ²	≥1.5	2.18	Pass
8	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
9	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
10	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
11	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
12	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
13	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
14	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass
15	Heat resistance (100°C, 2h)	—	No obvious deformation or discoloration after impact test.	Confirmed	Pass



Our Factory



Our Customer



Packaging



FAQ

***Bạn là nhà sản xuất hay thương nhân?**

***Vâng, chúng tôi là nhà sản xuất thực sự, Có rất nhiều hình ảnh trong phần giới thiệu công ty của chúng tôi. nếu bạn cần sản phẩm đặc biệt khác, chúng tôi sẽ cố gắng hết sức để giúp bạn, để chúng tôi có thể xây dựng mối quan hệ kinh doanh lâu dài.**

***Tôi có thể đặt hàng sản phẩm với tôi muốn hồ sơ?**

***Tất nhiên bạn có thể, chúng tôi cũng sẽ sản xuất các sản phẩm theo yêu cầu chi tiết của bạn.**

***Bạn có thể đặt thương hiệu của công ty tôi trên các sản phẩm của bạn?**

***Có, chúng tôi chấp nhận dịch vụ OEM & ODM. Nhưng chúng tôi cần một số thông tin về công ty của bạn.**

***Làm thế nào để cài đặt tấm lợp?**

***Vui lòng liên hệ với nhân viên dịch vụ của chúng tôi, chúng tôi có video cài đặt cho bạn.**

***Bạn có thể cung cấp mẫu cho tôi để mở thị trường và thử nghiệm phẩm chất?**

***Có, chúng tôi có thể. Chúng tôi có thể cung cấp mẫu miễn phí cho bạn, Bạn có thể trả chi phí vận chuyển không? Vui lòng liên hệ với nhân viên dịch vụ của chúng tôi.**

***Thuật ngữ thương mại của bạn là gì?**

*** Thanh toán: T / T trước 30%, số dư trước khi giao hàng.**

• Thời gian sản xuất: Trong vòng 7 ngày làm việc sau khi đặt cọc 30%

• Cảng vận chuyển FOB: Phật Sơn, Quảng Châu, Thâm Quyến

Contact us

 Tel:+86-13702632466

 Fax:0086-757-81848277

 Skype:jimhuang0.0

 Whatsapp:+86 137 0263 2466

 E-mails:sales08rooftile@zxc9999.com



 Add:Xiebian industrial Area,Danzao Town,Nanhai District,
Foshan City,Guangdong Province